

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

|   |    | HPG-I 04 DS Premium |
|---|----|---------------------|
|   |    | 202622              |
| Manufacturer  |    | STIEBEL ELTRON      |
| Heat source   |    | Brine               |
| Low temperature heat pump   |    | -                   |
| With booster heater   |    | x                   |
| Combi boiler with heat pump   |    | x                   |
| Rated heating output in colder climates for average temperature applications (Prated)           | kW | 4                   |
| Rated heating output in moderate climates for average temperature applications (Prated)         | kW | 4                   |
| Rated heating output in warmer climates for average temperature applications (Prated)           | kW | 4                   |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh)                          | kW | 2.27                |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 3.32                |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh)                           | kW | 1.38                |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 2.02                |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 3.76                |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh)                           | kW | 1.09                |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 1.3                 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 2.41                |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh)                          | kW | 1.09                |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 1.08                |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh)                          | kW | 1.08                |
| Tj = dual mode temperature in colder climates (Pdh)   | kW | 3.76                |
| Tj = dual mode temperature under moderate climatic conditions (Pdh)                             | kW | 3.76                |
| Tj = dual mode temperature in warmer climates (Pdh)   | kW | 3.76                |
| Tj = operating temperature limit in colder climates (Pdh)                                       | kW | 3.76                |
| Tj = operating temperature limit under moderate climatic conditions (Pdh)                       | kW | 3.76                |
| Tj = operating temperature limit in warmer climates (Pdh)                                       | kW | 3.76                |
| Dual mode temperature in colder climates (Tbiv)   | °C | -22                 |
| Dual mode temperature in moderate climates (Tbiv)   | °C | -10                 |
| Dual mode temperature in warmer climates (Tbiv)   | °C | 2                   |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs)   | %  | 156.8               |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | %  | 153                 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)   | %  | 146.7               |
| Tj = -7 °C COP, partial load range in colder climates (COPd)                                    |    | 4.1                 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 3.58                |
| Tj = 2 °C COP, partial load range in colder climates (COPd)                                     |    | 4.37                |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 4.22                |
| Tj = 2 °C COP, partial load range in warmer climates (COPd)                                     |    | 3.43                |
| Tj = 7 °C COP, partial load range in colder climates (COPd)                                     |    | 4.51                |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 4.47                |
| Tj = 7 °C COP, partial load range in warmer climates (COPd)                                     |    | 3.95                |
| Tj = 12 °C COP, partial load range in colder climates (COPd)                                    |    | 4.52                |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 4.49                |
| Tj = 12 °C COP, partial load range in warmer climates (COPd)                                    |    | 4.39                |
| Tj = dual mode temperature in colder climates (COPd)  |    | 3.43                |
| Tj = dual mode temperature under moderate climatic conditions (COPd)                            |    | 3.43                |
| Tj = dual mode temperature in warmer climates (COPd)  |    | 3.43                |

|   |   |          |
|---|---|----------|
| Tj = operating temperature limit in colder climates (COPd)                                |   | 3.43     |
| Tj = operating temperature limit under moderate climatic conditions (COPd)                |   | 3.43     |
| Tj = operating temperature limit in warmer climates (COPd)                                |   | 3.43     |
| Operating temperature limit in moderate climates (TOL)                                    | °C  | -10      |
| Heating water operating temperature limit (WTOL)  | °C  | 75       |
| Power consumption, OFF state (Poff)   | W   | 16       |
| Power consumption, thermostat OFF state (PTO)   | W   | 16       |
| Standby power consumption (PSB)   | W   | 16       |
| Power consumption, operating state, with crankcase heating (PCK)                          | W   | 0        |
| Booster heater heating output in colder climates (Psup)                                   | kW  | 0        |
| Booster heater heating output in moderate climate (Psup)                                  | kW  | 0.00     |
| Booster heater heating output in warmer climates (Psup)                                   | kW  | 0        |
| Type of energy supply, booster heater   |   | electric |
| Power control   |   | variable |
| Sound power level internal  | dB(A)   | 43       |
| Annual energy consumption in colder climates for average temperature applications (QHE)   | kWh/a   | 2252     |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a   | 1934     |
| Annual energy consumption in warmer climates for average temperature applications (QHE)   | kWh/a   | 1300     |
| Flow rate, heat source side   | m <sup>3</sup> /h   | 0,5      |
| Load profile  |   | XL       |
| Daily power consumption in colder climates (QELEC)  | kWh   | 7.08     |
| Daily power consumption (Qelec)   | kWh   | 7.08     |
| Daily power consumption in warmer climates (QELEC)  | kWh   | 7.08     |
| Annual power consumption in colder climates (AEC)   | kWh/a   | 1556     |
| Annual power consumption in moderate climates (AEC)                                       | kWh/a   | 1556     |
| Annual power consumption in warmer climates (AEC)   | kWh/a   | 1556     |
| Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions    | %   | 108      |
| Special measures  | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |          |