

Product datasheet: Mechanical ventilation unit to Regulation (EU) No. 1254/2014 | 1253/2014

		VRC-W 450 E Premium CN
		206746
Manufacturer		STIEBEL ELTRON
Specific energy consumption under colder climate conditions with manual control	kWh/(m²a)	-70,70
Specific energy consumption under average climate conditions with manual control	kWh/(m²a)	-35,91
Specific energy consumption under warmer climate conditions with manual control	kWh/(m²a)	-13,35
Energy efficiency class under colder climate conditions with manual control		A+
Energy efficiency class under average climate conditions with manual control		A
Energy efficiency class under warmer climate conditions with manual control		E
Ventilation unit type		WLA, Zwei Richtungen
Drive type		Drehzahl geregelt
Heat recovery type		Rekuperativ
Rate of temperature change for heat recovery	%	78,0
Max. air flow rate	m³/h	450
Max. power consumption	W	120
Sound power level LWA	dB(A)	49
Reference air flow rate	m³/s	0,087
Reference pressure differential	Pa	50
Specific power input	W/(m³/h)	0,18
Control factor, manual control		1,00
Internal air leakage quota	%	2,00
External air leakage quota	%	2,50
Filter change indicator		Visual filter change warning signal on the remote control display
Instructions for controllable outdoor air grilles with ELA		not applicable
Annual power consumption under colder climate conditions with manual control	kWh/a	807
Annual power consumption under average climate conditions with manual control	kWh/a	270
Annual power consumption under warmer climate conditions with manual control	kWh/a	225
Annual heating savings under colder climate conditions with manual control	kWh/a	8216
Annual heating savings under average climate conditions with manual control	kWh/a	4200
Annual heating savings under warmer climate conditions with manual control	kWh/a	1899