

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | WPC 04 |
|-------------------------------------------------------------------------------------------------|----|----------------|
| | | 232926 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Brine |
| Low temperature heat pump | | - |
| With booster heater | | x |
| Combi boiler with heat pump | | x |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 5 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 4 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 4 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 4.5 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 4.30 |
| Tj = -7 °C heating output, partial load range in warmer climates (Pdh) | kW | 4.3 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 4.6 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 4.50 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 4.3 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 4.7 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 4.60 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 4.4 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 4.7 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 4.70 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 4.6 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 4.4 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 4.30 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 4.3 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 4.3 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 4.30 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 4.3 |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh) | kW | 4.30 |
| Dual mode temperature in colder climates (Tbiv) | °C | -15 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -10 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | 133 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | 128 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | 126 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 3.34 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 2.85 |
| Tj = -7 °C COP, partial load range in warmer climates (COPd) | | 2.72 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 3.73 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.35 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 2.72 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 4.09 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.73 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 3.11 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 4.39 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.18 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 3.87 |

| | | |
|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------|
| Tj = dual mode temperature in colder climates (COPd) | | 3.12 |
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 2.72 |
| Tj = dual mode temperature in warmer climates (COPd) | | 2.72 |
| Tj = operating temperature limit in colder climates (COPd) | | 2.72 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 2.72 |
| Tj = operating temperature limit in warmer climates (COPd) | | 2.72 |
| For air/water heat pumps: Tj= -15 °C (if TOL < -20 °C) (COPd) | | 2.72 |
| Operating temperature limit in moderate climates (TOL) | °C | -10 |
| Heating water operating temperature limit (WTOL) | °C | 65 |
| Power consumption, OFF state (Poff) | W | 0 |
| Power consumption, thermostat OFF state (PTO) | W | 54 |
| Standby power consumption (PSB) | W | 9 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 0 |
| Booster heater heating output in moderate climate (Psup) | kW | 0.00 |
| Type of energy supply, booster heater | | electric |
| Power control | | Fixed |
| Sound power level external | dB(A) | 0 |
| Sound power level internal | dB(A) | 43 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 3774 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 2583 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 1690 |
| Flow rate, heat source side | m ³ /h | 1,15 |
| Load profile | | XL |
| Daily power consumption in colder climates (QELEC) | kWh | 6.68 |
| Daily power consumption (Qelec) | kWh | 6.68 |
| Daily power consumption in warmer climates (QELEC) | kWh | 6.68 |
| Annual power consumption in colder climates (AEC) | kWh/a | 1458 |
| Annual power consumption in moderate climates (AEC) | kWh/a | 1458 |
| Annual power consumption in warmer climates (AEC) | kWh/a | 1458 |
| Energy efficiency for DHW heating (Γ_{wh}) under moderate climatic conditions | % | 116 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |