

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

|   |    | WPE-I 12 HW 230 GB Premium |
|---|----|----------------------------|
|   |    | 202640                     |
| Manufacturer  |    | STIEBEL ELTRON             |
| Heat source   |    | Brine                      |
| Low temperature heat pump   |    | -                          |
| With booster heater   |    | x                          |
| Combi boiler with heat pump   |    | x                          |
| Rated heating output in colder climates for average temperature applications (Prated)           | kW | 12                         |
| Rated heating output in moderate climates for average temperature applications (Prated)         | kW | 12                         |
| Rated heating output in warmer climates for average temperature applications (Prated)           | kW | 12                         |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh)                          | kW | 7.24                       |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 10.59                      |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh)                           | kW | 4.4                        |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 6.44                       |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 11.99                      |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh)                           | kW | 2.82                       |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 4.13                       |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 7.69                       |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh)                          | kW | 2.23                       |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 2.21                       |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh)                          | kW | 3.41                       |
| Tj = dual mode temperature in colder climates (Pdh)   | kW | 11.99                      |
| Tj = dual mode temperature under moderate climatic conditions (Pdh)                             | kW | 11.99                      |
| Tj = dual mode temperature in warmer climates (Pdh)   | kW | 11.99                      |
| Tj = operating temperature limit in colder climates (Pdh)                                       | kW | 11.99                      |
| Tj = operating temperature limit under moderate climatic conditions (Pdh)                       | kW | 11.99                      |
| Tj = operating temperature limit in warmer climates (Pdh)                                       | kW | 11.99                      |
| Dual mode temperature in colder climates (Tbiv)   | °C | -22                        |
| Dual mode temperature in moderate climates (Tbiv)   | °C | -10                        |
| Dual mode temperature in warmer climates (Tbiv)   | °C | 2                          |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs)   | %  | 174.3                      |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | %  | 169                        |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)   | %  | 167.6                      |
| Tj = -7 °C COP, partial load range in colder climates (COPd)                                    |    | 4.31                       |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 3.55                       |
| Tj = 2 °C COP, partial load range in colder climates (COPd)                                     |    | 4.91                       |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 4.49                       |
| Tj = 2 °C COP, partial load range in warmer climates (COPd)                                     |    | 3.29                       |
| Tj = 7 °C COP, partial load range in colder climates (COPd)                                     |    | 5.16                       |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 4.99                       |
| Tj = 7 °C COP, partial load range in warmer climates (COPd)                                     |    | 4.12                       |
| Tj = 12 °C COP, partial load range in colder climates (COPd)                                    |    | 5.4                        |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 5,25                       |
| Tj = 12 °C COP, partial load range in warmer climates (COPd)                                    |    | 5.1                        |
| Tj = dual mode temperature in colder climates (COPd)  |    | 3.29                       |
| Tj = dual mode temperature under moderate climatic conditions (COPd)                            |    | 3.29                       |
| Tj = dual mode temperature in warmer climates (COPd)  |    | 3.29                       |

|   |   |          |
|---|---|----------|
| T <sub>j</sub> = operating temperature limit in colder climates (COP <sub>d</sub> )                 |   | 3.29     |
| T <sub>j</sub> = operating temperature limit under moderate climatic conditions (COP <sub>d</sub> ) |   | 3.29     |
| T <sub>j</sub> = operating temperature limit in warmer climates (COP <sub>d</sub> )                 |   | 3.29     |
| Operating temperature limit in moderate climates (TOL)  | °C  | -10      |
| Heating water operating temperature limit (WTOL)  | °C  | 75       |
| Power consumption, OFF state (P <sub>off</sub> )  | W   | 19       |
| Power consumption, thermostat OFF state (PTO)   | W   | 19       |
| Standby power consumption (PSB)   | W   | 19       |
| Power consumption, operating state, with crankcase heating (PCK)                                    | W   | 0        |
| Booster heater heating output in colder climates (P <sub>sup</sub> )                                | kW  | 0        |
| Booster heater heating output in moderate climate (P <sub>sup</sub> )                               | kW  | 0.00     |
| Booster heater heating output in warmer climates (P <sub>sup</sub> )                                | kW  | 0        |
| Type of energy supply, booster heater   |   | electric |
| Power control   |   | variable |
| Sound power level internal  | dB(A)   | 44       |
| Annual energy consumption in colder climates for average temperature applications (QHE)             | kWh/a   | 6485     |
| Annual energy consumption in moderate climates for average temperature applications (QHE)           | kWh/a   | 5607     |
| Annual energy consumption in warmer climates for average temperature applications (QHE)             | kWh/a   | 3650     |
| Flow rate, heat source side   | m <sup>3</sup> /h   | 1,08     |
| Load profile  |   | XL       |
| Daily power consumption in colder climates (QELEC)  | kWh   | 6.61     |
| Daily power consumption (Qelec)   | kWh   | 6.61     |
| Daily power consumption in warmer climates (QELEC)  | kWh   | 6.61     |
| Annual power consumption in colder climates (AEC)   | kWh/a   | 1451     |
| Annual power consumption in moderate climates (AEC)   | kWh/a   | 1451     |
| Annual power consumption in warmer climates (AEC)   | kWh/a   | 1451     |
| Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions              | %   | 115      |
| Special measures  | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |          |