

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | HPA-O 07.1 CS Premium |
|---|----|-----------------------|
| | | 202668 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Outside air |
| Low temperature heat pump | | - |
| With booster heater | | x |
| Combi boiler with heat pump | | - |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 12 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 8 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 4 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 7.2 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 7.0 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 4.4 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 4.3 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 4.3 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 3.1 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 3.0 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 2.8 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 3.7 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 3.6 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 3.5 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 7.2 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 7.0 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 4.3 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 5.0 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 6.5 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 4.3 |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh) | kW | 6.3 |
| Dual mode temperature in colder climates (Tbiv) | °C | -7 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -7 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | 128 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | 153 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | 163 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 2.70 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 2.43 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 4.31 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.79 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 2.93 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 5.99 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 5.22 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 3.90 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 6.88 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 6.33 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 5.53 |
| Tj = dual mode temperature in colder climates (COPd) | | 2.70 |
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 2.43 |

| | | |
|---|-------------------|----------|
| Tj = dual mode temperature in warmer climates (COPd) | | 2.93 |
| Tj = operating temperature limit in colder climates (COPd) | | 1.78 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 2.14 |
| Tj = operating temperature limit in warmer climates (COPd) | | 2.93 |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd) | | 2.22 |
| Operating temperature limit in colder climates (TOL) | °C | -22 |
| Operating temperature limit in moderate climates (TOL) | °C | -10 |
| Operating temperature limit in warmer climates (TOL) | °C | 2 |
| Heating water operating temperature limit in colder climates (WTOL) | °C | 75 |
| Heating water operating temperature limit (WTOL) | °C | 75 |
| Heating water operating temperature limit in warmer climates (WTOL) | °C | 75 |
| Power consumption, OFF state (Poff) | W | 12 |
| Power consumption, thermostat OFF state (PTO) | W | 10 |
| Standby power consumption (PSB) | W | 12 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 10 |
| Booster heater heating output in colder climates (Psup) | kW | 6.9 |
| Booster heater heating output in moderate climate (Psup) | kW | 1.4 |
| Booster heater heating output in warmer climates (Psup) | kW | 0.0 |
| Type of energy supply, booster heater | | electric |
| Power control | | variable |
| Sound power level external | dB(A) | 48 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 9005 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 4219 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 1388 |
| Flow rate, heat source side | m ³ /h | 2250 |

Special measures

For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions