

Технические характеристики изделия:

|              |    | HPG-I 06 CS Premium |
|--------------|----|---------------------|
|              |    | 202628              |
| Manufacturer |    | STIEBEL ELTRON      |
|              |    | Sole                |
|              |    | -                   |
|              |    | x                   |
|              |    | -                   |
|              | kW | 6                   |
|              | kW | 6                   |
|              | kW | 6                   |
|              | kW | 3,7                 |
|              | kW | 5,3                 |
|              | kW | 2,2                 |
|              | kW | 3,3                 |
|              | kW | 6,1                 |
|              | kW | 1,4                 |
|              | kW | 2,1                 |
|              | kW | 3,9                 |
|              | kW | 1,1                 |
|              | kW | 1,1                 |
|              | kW | 1,7                 |
|              | kW | 6,1                 |
|              | kW | 6,1                 |
|              | kW | 6,1                 |
|              | kW | 6,1                 |
|              | kW | 6,1                 |
|              | kW | 6,1                 |
|              | °C | -22                 |
|              | °C | -10                 |
|              | °C | 2                   |
|              | %  | 166                 |
|              | %  | 159                 |
|              | %  | 158                 |
|              |    | 4,15                |
|              |    | 3,55                |
|              |    | 4,68                |
|              |    | 4,27                |
|              |    | 3,34                |
|              |    | 4,80                |
|              |    | 4,76                |
|              |    | 3,97                |
|              |    | 4,73                |
|              |    | 4,61                |
|              |    | 4,81                |
|              |    | 3,34                |
|              |    | 3,34                |
|              |    | 3,34                |
|              |    | 3,34                |
|              |    | 3,34                |
|              | °C | -22                 |
|              | °C | -10                 |
|              | °C | 2                   |
|              | °C | 75                  |
|              | °C | 75                  |
|              | °C | 75                  |
|              | W  | 16                  |
|              | W  | 16                  |

|  |       |              |
|--|-------|--------------|
|  | W     | 16           |
|  | W     | 0            |
|  | kW    | 0,0          |
|  | kW    | 0,0          |
|  | kW    | 0,0          |
|  |       | elektrisch   |
|  |       | veränderlich |
|  | dB(A) | 0            |
|  | dB(A) | 41           |
|  | kWh/a | 3439         |
|  | kWh/a | 2988         |
|  | kWh/a | 1954         |
|  | m³/h  | 6            |