

Технические характеристики изделия:

|              |    | LWZ 07.1 Premium HKWL 230 |
|--------------|----|---------------------------|
|              |    | 206281                    |
| Manufacturer |    | STIEBEL ELTRON            |
|              |    | Luft                      |
|              |    | x                         |
|              |    | x                         |
|              |    | x                         |
|              | kW | 7                         |
|              | kW | 7                         |
|              | kW | 4                         |
|              | kW | 6,4                       |
|              | kW | 6,4                       |
|              | kW | 3,9                       |
|              | kW | 3,9                       |
|              | kW | 8,3                       |
|              | kW | 2,8                       |
|              | kW | 2,4                       |
|              | kW | 5,4                       |
|              | kW | 3,2                       |
|              | kW | 2,6                       |
|              | kW | 3,2                       |
|              | kW | 6,4                       |
|              | kW | 6,4                       |
|              | kW | 8,3                       |
|              | kW | 3,0                       |
|              | kW | 6,0                       |
|              | kW | 8,3                       |
|              | kW | 5,6                       |
|              | °C | -10                       |
|              | °C | -7                        |
|              | °C | 2                         |
|              | %  | 118                       |
|              | %  | 128                       |
|              | %  | 145                       |
|              |    | 2,50                      |
|              |    | 2,24                      |
|              |    | 3,48                      |
|              |    | 3,13                      |
|              |    | 2,34                      |
|              |    | 4,68                      |
|              |    | 4,27                      |
|              |    | 3,26                      |
|              |    | 5,67                      |
|              |    | 5,24                      |
|              |    | 5,11                      |
|              |    | 2,50                      |
|              |    | 2,24                      |
|              |    | 2,34                      |
|              |    | 1,46                      |
|              |    | 2,06                      |
|              |    | 2,34                      |
|              |    | 2,08                      |
|              | °C | -22                       |
|              | °C | -10                       |
|              | °C | 2                         |
|              | °C | 63                        |
|              | °C | 75                        |
|              | °C | 75                        |

|  |       |              |
|--|-------|--------------|
|  | W     | 19           |
|  | W     | 15           |
|  | W     | 19           |
|  | W     | 2            |
|  | kW    | 3,9          |
|  | kW    | 1,2          |
|  |       | elektrisch   |
|  |       | veränderlich |
|  | dB(A) | 56           |
|  | dB(A) | 53           |
|  | kWh/a | 5646         |
|  | kWh/a | 4199         |
|  | kWh/a | 1411         |
|  |       | XL           |
|  | kWh   | 6,350        |
|  | kWh   | 2042,000     |
|  | kWh   | 1397,000     |
|  | kWh   | 1183,000     |
|  | %     | 84           |
|  | %     | 120          |
|  | %     | 145          |