

Технические характеристики изделия:

|              |    | WPL 17 ICS classic |
|--------------|----|--------------------|
|              |    | 236376             |
| Manufacturer |    | STIEBEL ELTRON     |
|              |    | Luft               |
|              |    | -                  |
|              |    | x                  |
|              |    | -                  |
|              | kW | 13                 |
|              | kW | 7                  |
|              | kW | 4                  |
|              | kW | 7,8                |
|              | kW | 6,4                |
|              | kW | 5,0                |
|              | kW | 4,8                |
|              | kW | 4,4                |
|              | kW | 4,3                |
|              | kW | 4,2                |
|              | kW | 4,0                |
|              | kW | 3,3                |
|              | kW | 3,2                |
|              | kW | 3,0                |
|              | kW | 7,8                |
|              | kW | 6,4                |
|              | kW | 4,4                |
|              | kW | 5,2                |
|              | kW | 2,8                |
|              | kW | 4,4                |
|              | kW | 0,0                |
|              | °C | -7                 |
|              | °C | -7                 |
|              | °C | 2                  |
|              | %  | 111                |
|              | %  | 129                |
|              | %  | 145                |
|              |    | 2,31               |
|              |    | 2,17               |
|              |    | 3,61               |
|              |    | 3,14               |
|              |    | 2,27               |
|              |    | 4,98               |
|              |    | 4,56               |
|              |    | 3,30               |
|              |    | 6,88               |
|              |    | 633,00             |
|              |    | 5,35               |
|              |    | 2,31               |
|              |    | 2,17               |
|              |    | 2,21               |
|              |    | 2,33               |
|              |    | 1,83               |
|              |    | 2,21               |
|              |    | 0,00               |
|              | °C | -20                |
|              | °C | -10                |
|              | °C | 2                  |
|              | °C | 60                 |
|              | °C | 60                 |
|              | °C | 60                 |

|  |       |              |
|--|-------|--------------|
|  | W     | 21           |
|  | W     | 56           |
|  | W     | 56           |
|  | W     | 26           |
|  | kW    | 4,4          |
|  |       | elektrisch   |
|  |       | veränderlich |
|  | dB(A) | 48           |
|  | dB(A) | 51           |
|  | kWh/a | 11197        |
|  | kWh/a | 4506         |
|  | kWh/a | 1592         |
|  | m³/h  | 1240         |