

Технические характеристики изделия:

|              |    | WPL 15 AS      |
|--------------|----|----------------|
|              |    | 236638         |
| Manufacturer |    | STIEBEL ELTRON |
|              |    | Außenluft      |
|              |    | -              |
|              |    | x              |
|              |    | -              |
|              | kW | 12             |
|              | kW | 8              |
|              | kW | 4              |
|              | kW | 7,0            |
|              | kW | 7,1            |
|              | kW | 4,2            |
|              | kW | 4,2            |
|              | kW | 4,0            |
|              | kW | 4,3            |
|              | kW | 4,2            |
|              | kW | 3,9            |
|              | kW | 4,1            |
|              | kW | 4,0            |
|              | kW | 3,8            |
|              | kW | 7,9            |
|              | kW | 7,4            |
|              | kW | 4,0            |
|              | kW | 11,4           |
|              | kW | 7,0            |
|              | kW | 4,0            |
|              | kW | 7,0            |
|              | °C | -10            |
|              | °C | -8             |
|              | °C | 2              |
|              | %  | 118            |
|              | %  | 122            |
|              | %  | 120            |
|              |    | 2,45           |
|              |    | 2,18           |
|              |    | 3,70           |
|              |    | 3,30           |
|              |    | 2,50           |
|              |    | 4,53           |
|              |    | 4,07           |
|              |    | 3,16           |
|              |    | 5,44           |
|              |    | 514,00         |
|              |    | 4,57           |
|              |    | 2,28           |
|              |    | 2,13           |
|              |    | 2,50           |
|              |    | 1,97           |
|              |    | 1,97           |
|              |    | 2,50           |
|              |    | 1,97           |
|              | °C | -20            |
|              | °C | -10            |
|              | °C | 2              |
|              | °C | 65             |
|              | °C | 65             |
|              | °C | 65             |

|  |       |              |
|--|-------|--------------|
|  | W     | 16           |
|  | W     | 16           |
|  | W     | 16           |
|  | W     | 43           |
|  | kW    | 2,3          |
|  | kW    | 1,0          |
|  | kW    | 0,0          |
|  |       | elektrisch   |
|  |       | veränderlich |
|  | dB(A) | 50           |
|  | kWh/a | 9481         |
|  | kWh/a | 5300         |
|  | kWh/a | 1750         |
|  | m³/h  | 2300         |