



ENERG
енергия · ενεργεια



STIEBEL ELTRON

WPL-A 07 H 230 Premium




55 °C

35 °C



A⁺⁺

A⁺⁺⁺



2019

■ 12

■ 8

■ 4

kW

■ 12

■ 8

■ 4

kW



811/2013

		WPL-A 07 H 230 Premium
		200127
Manufacturer		STIEBEL ELTRON
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	8
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	8
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	151
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	189
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	4280
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	3474
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	12
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	12
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	4
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	4
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	127
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)	%	150
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	154
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	214
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	9041
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	7611
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	1462
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	1058




ENERG
енергия · ενεργεια



WPL-A 07 H 230 Premium

STIEBEL ELTRON



A⁺⁺

A⁺⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺

A

B

C


D

E

F

G

+



+



+



+



Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		WPL-A 07 H 230 Premium
		200127
Manufacturer		STIEBEL ELTRON
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	189
Temperature control class		VI
Contribution of temperature control to space heating energy efficiency	%	4
Space heating energy efficiency of package under average climate conditions	%	155
Space heating energy efficiency of package under colder climate conditions	%	131
Space heating energy efficiency of package under warmer climate conditions	%	158
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	24
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	4
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A+++

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		WPL-A 07 H 230 Premium
		200127
Manufacturer		STIEBEL ELTRON
Heat source		Außenluft
Low temperature heat pump		-
With auxiliary heater		x
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	12
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	8
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	4
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	7,2
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	7,0
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	4,4
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	4,3
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	4,3
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	3,1
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	3,0
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	2,8
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	3,7
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	3,6
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	3,5
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	7,2
Tj = dual mode temperature under average climate conditions (Pdh)	kW	7,0
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	4,3
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	5,0
Tj = operating temperature limit under average climate conditions (Pdh)	kW	6,5
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	4,3
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	6,3
Dual mode temperature under colder climate conditions (Tbiv)	°C	-7
Dual mode temperature under average climate conditions (Tbiv)	°C	-7
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	127
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	151
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	154
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		2,70
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		2,43
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		4,31
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		3,79
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,93
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		5,99
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		5,22

Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,90
Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		6,88
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		633,00
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		5,53
Tj = dual mode temperature under colder climate conditions (COPd)		2,70
Tj = dual mode temperature under average climate conditions (COPd)		2,43
Tj = dual mode temperature under warmer climate conditions (COPd)		2,93
Tj = operating temperature limit under colder climate conditions (COPd)		1,78
Tj = operating temperature limit under average climate conditions (COPd)		2,14
Tj = operating temperature limit under warmer climate conditions (COPd)		2,93
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		2,22
Operating temperature limit under colder climate conditions (TOL)	°C	-22
Operating temperature limit under average climate conditions (TOL)	°C	-10
Operating temperature limit under warmer climate conditions (TOL)	°C	2
Operating temperature limit of heating water under colder climate conditions (WTOL)	°C	75
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	75
Operating temperature limit of heating water under warmer climate conditions (WTOL)	°C	75
Power consumption, off-mode (Poff)	W	12
Power consumption, thermostat off-mode (PTO)	W	17
Power consumption, standby state (PSB)	W	12
Power consumption, operating state, with crankcase heating (PCK)	W	4
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	kW	6,9
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	1,4
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	kW	0,0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	9041
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	4280
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	1462
Flow rate on heat source side	m³/h	2250