




**ENERG** Y IJA  
енергия · ενέργεια IE IA

**STIEBEL ELTRON**

VRC-W 600  
Premium manual



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**

		<b>VRC-W 600 Premium</b>
		204714
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, manual control	kWh/(m <sup>2</sup> p.a.)	-75.12
Specific energy consumption in average climates, manual control	kWh/(m <sup>2</sup> p.a.)	-37.40
Specific energy consumption in warmer climates, manual control	kWh/(m <sup>2</sup> p.a.)	-13.17
Energy efficiency class in colder climates, manual control		A+
Energy efficiency class in average climates, manual control		A
Energy efficiency class in warmer climates, manual control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	87.6
Max. air flow rate	m <sup>3</sup> /h	600
Max. power consumption	W	251.8
Sound power level Lwa	dB(A)	54
Reference air flow rate	m <sup>3</sup> /s	0.117
Reference pressure differential	Pa	50
Specific input	W/(m <sup>3</sup> /h)	0.23
Control factor, manual control		1
Declared maximum internal leakage rates	%	0,78
Declared maximum external leakage rates	%	0.59
Annual power consumption in colder climates with manual control	kWh/a	870
Annual power consumption in average climates with manual control	kWh/a	333
Annual power consumption in warmer climates with manual control	kWh/a	288
Annual heating savings in colder climates with manual control	kWh/a	8814
Annual heating savings in average climates with manual control	kWh/a	4505
Annual heating savings in warmer climates with manual control	kWh/a	2037



**ENERG** Y IJA  
енергия · ενέργεια IE IA

**STIEBEL ELTRON**

VRC-W 600  
Premium clock



**54**  
dB

**600 m<sup>3</sup>/h**

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**


		<b>VRC-W 600 Premium</b>
		204714
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, time control	kWh/(m <sup>2</sup> p.a.)	-76.20
Specific energy consumption in average climates, time control	kWh/(m <sup>2</sup> p.a.)	-38.30
Specific energy consumption in warmer climates, time control	kWh/(m <sup>2</sup> p.a.)	-13.98
Energy efficiency class in colder climates, time control		A+
Energy efficiency class in average climates, time control		A
Energy efficiency class in warmer climates, time control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	87.6
Max. air flow rate	m <sup>3</sup> /h	600
Max. power consumption	W	251.8
Sound power level Lwa	dB(A)	54
Reference air flow rate	m <sup>3</sup> /s	0.117
Reference pressure differential	Pa	50
Specific input	W/(m <sup>3</sup> /h)	0.23
Control factor, time control		0,95
Declared maximum internal leakage rates	%	0,78
Declared maximum external leakage rates	%	0.59
Annual power consumption in colder climates with time control	kWh/a	842
Annual power consumption in average climates with time control	kWh/a	305
Annual power consumption in warmer climates with time control	kWh/a	260
Annual heating savings in colder climates with time control	kWh/a	8852
Annual heating savings in average climates with time control	kWh/a	4525
Annual heating savings in warmer climates with time control	kWh/a	2046



**ENERG** Y IJA  
енергия · ενέργεια IE IA

**STIEBEL ELTRON**

VRC-W 600  
Premium sensor



**54**  
dB

**600 m<sup>3</sup>/h**

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**


		VRC-W 600 Premium
		204714
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-78.27
Specific energy consumption in average climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-39.99
Specific energy consumption in warmer climates, central demand-dependent control	kWh/(m <sup>2</sup> p.a.)	-15.44
Energy efficiency class in colder climates, central demand-dependent control		A+
Energy efficiency class in average climates, central demand-dependent control		A
Energy efficiency class in warmer climates, central demand-dependent control		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	87.6
Max. air flow rate	m <sup>3</sup> /h	600
Max. power consumption	W	251.8
Sound power level L <sub>wa</sub>	dB(A)	54
Reference air flow rate	m <sup>3</sup> /s	0.117
Reference pressure differential	Pa	50
Specific input	W/(m <sup>3</sup> /h)	0.23
Control factor, central demand-dependent control		0.85
Declared maximum internal leakage rates	%	0.78
Declared maximum external leakage rates	%	0.59
Annual power consumption in colder climates with central demand-dependent control	kWh/a	790
Annual power consumption in average climates with central demand-dependent control	kWh/a	253
Annual power consumption in warmer climates with central demand-dependent control	kWh/a	208
Annual heating savings in colder climates with central demand-dependent control	kWh/a	8930
Annual heating savings in average climates with central demand-dependent control	kWh/a	4565
Annual heating savings in warmer climates with central demand-dependent control	kWh/a	2064



**ENERG** Y IJA  
енергия · ενέργεια IE IA

**STIEBEL ELTRON**

VRC-W 600  
Premium sensors



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

**Product datasheet: Mechanical ventilation units to regulation (EU) no. 1254/2014 | 1253/2014**

		<b>VRC-W 600 Premium</b>
		204714
Manufacturer		STIEBEL ELTRON
Specific energy consumption in colder climates, control subject to on-site requirements	kWh/(m <sup>2</sup> p.a.)	-81.98
Specific energy consumption in average climates, control subject to on-site requirements	kWh/(m <sup>2</sup> p.a.)	-42.94
Specific energy consumption in warmer climates, control subject to on-site requirements	kWh/(m <sup>2</sup> p.a.)	-17.95
Energy efficiency class in colder climates, control subject to on-site requirements		A+
Energy efficiency class in average climates, control subject to on-site requirements		A+
Energy efficiency class in warmer climates, control subject to on-site requirements		E
Ventilation unit type		WLA, Two directions
Drive type		Variable speed
Heat recovery method		Recovery
Rate of temperature change for heat recovery	%	87.6
Max. air flow rate	m <sup>3</sup> /h	600
Max. power consumption	W	251.8
Sound power level L <sub>wa</sub>	dB(A)	54
Reference air flow rate	m <sup>3</sup> /s	0.117
Reference pressure differential	Pa	50
Specific input	W/(m <sup>3</sup> /h)	0.23
Control factor, control subject to on-site requirements		0.65
Declared maximum internal leakage rates	%	0.78
Declared maximum external leakage rates	%	0.59
Annual power consumption in colder climates with control subject to on-site requirements	kWh/a	704
Annual power consumption in average climates with control subject to on-site requirements	kWh/a	167
Annual power consumption in warmer climates with control subject to on-site requirements	kWh/a	122
Annual heating savings in colder climates with control subject to on-site requirements	kWh/a	9084
Annual heating savings in average climates with control subject to on-site requirements	kWh/a	4644
Annual heating savings in warmer climates with control subject to on-site requirements	kWh/a	2100