



ENERG Y IJA
 енергия · ενέργεια IE IA

STIEBEL ELTRON WPF 13 basic



55 °C

35 °C



A+

A+++

53 dB

■ 15	■ 16
■ 12	■ 13
■ 12	■ 13
kW	kW

2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		WPF 13 basic
		230947
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Rated heating output in moderate climates for medium temperature applications	kW	12
Rated heating output in moderate climates for low temperature applications	kW	13
Energy efficiency for central heating in moderate climates for medium temperature applications	%	122
Energy efficiency for central heating in moderate climates for low temperature applications	%	189
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	7350
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	5285
Sound power level internal	dB(A)	53
Rated heating output in colder climates for medium temperature applications	kW	15
Rated heating output in colder climates for low temperature applications	kW	16
Rated heating output in warmer climates for medium temperature applications	kW	12
Rated heating output in warmer climates for low temperature applications	kW	13
Energy efficiency for central heating in colder climates for medium temperature applications	%	128
Energy efficiency for central heating in colder climates for low temperature applications	%	196
Energy efficiency for central heating in warmer climates for medium temperature applications	%	122
Energy efficiency for central heating in warmer climates for low temperature applications	%	189
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	10595
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	7542
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	4755
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	3407



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

WPF 13 basic



A⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

+		<input type="checkbox"/>
+		<input type="checkbox"/>
+		<input checked="" type="checkbox"/>
+		<input type="checkbox"/>

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		WPF 13 basic
		230947
Manufacturer		STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications	%	122
Temperature controller class		VII
Contribution of temperature controller to room heating energy efficiency	%	3,50
Room heating energy efficiency of composite system under moderate climatic conditions	%	126
Room heating energy efficiency of composite system under colder climatic conditions	%	132
Room heating energy efficiency of composite system under warmer climatic conditions	%	126
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	6
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	0
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013

		WPF 13 basic
		230947
Manufacturer		STIEBEL ELTRON
Heat source		Brine
Low temperature heat pump		-
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in colder climates for medium temperature applications	kW	15
Rated heating output in moderate climates for medium temperature applications	kW	12
Rated heating output in warmer climates for medium temperature applications	kW	12
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	11,70
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	12,00
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	12,30
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	12,50
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	11,60
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	11,60
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	11,60
{Bivalenttemperatur bei durchschnittlichen Klimaverhältnissen (Tbiv)}	°C	-10
Energy efficiency for central heating in colder climates for medium temperature applications	%	128
Energy efficiency for central heating in moderate climates for medium temperature applications	%	122
Energy efficiency for central heating in warmer climates for medium temperature applications	%	122
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2,96
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,20
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		3,60
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		4,09
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,57
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,57
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		2,57
Heating water operating temperature limit (WTOL)	°C	60
Power consumption, OFF state (Poff)	W	0,000
Power consumption, thermostat OFF state (PTO)	W	78
Standby power consumption (PSB)	W	3,000
Power consumption, operating state, with crankcase heating (PCK)	W	0,000
Booster heater heating output (PSUB)	kW	0,000
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level internal	dB(A)	53
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	10595
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	7350
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	4755
Flow rate, heat source side	m ³ /h	3,1