



ENERG Y IJA
 енергия · ενεργεια IE IA

STIEBEL ELTRON WPE-I 15 HK 230
 Premium



55 °C

35 °C



39 dB

Icon of a house with sound waves emanating from it, and a smaller icon of a house with sound waves entering it.

■ 14 ■ 14
 ■ 14 ■ 14
 ■ 14 ■ 14
 kW kW

Map of Europe with various countries shaded in different intensities of blue.

2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)

| | | WPE-I 15 HK 230 Premium |
|---|-------|---|
| | | 238617 |
| Manufacturer | | STIEBEL ELTRON |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A+++ |
| Energy efficiency class for central heating in moderate climates for low temperature applications | | A+++ |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 14 |
| Rated heating output in moderate climates for low temperature applications (Prated) | kW | 14 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 168 |
| Seasonal room heating efficiency in moderate climates for low temperature applications (η_s) | % | 210 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 6476 |
| Annual energy consumption in moderate climates for low temperature applications (QHE) | kWh/a | 5489 |
| Sound power level internal | dB(A) | 39 |
| Special measures | | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 14 |
| Rated heating output in colder climates for low temperature applications (Prated) | kW | 14 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 14 |
| Rated heating output in warmer climates for low temperature applications (Prated) | kW | 14 |
| Seasonal room heating efficiency in colder climates for average temperature applications (η_s) | % | 174.2 |
| Seasonal room heating efficiency in colder climates for low temperature applications (η_s) | % | 218.4 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (η_s) | % | 166.7 |
| Seasonal room heating efficiency in warmer climates for low temperature applications (η_s) | % | 208.3 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 7451 |
| Annual energy consumption in colder climates for low temperature applications (QHE) | kWh/a | 6298 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 4211 |
| Annual energy consumption in warmer climates for low temperature applications (QHE) | kWh/a | 3573 |



ENERG

енергия · ενεργεια

Y

IJA



IE

IA

STIEBEL ELTRON

WPE-I 15 HK 230 Premium



+ 
 + 
 + 
 + 














Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)

| | | WPE-I 15 HK 230 Premium |
|---|---|--------------------------------|
| | | 238617 |
| Manufacturer | | STIEBEL ELTRON |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 168 |
| Contribution of temperature controller to room heating energy efficiency | % | 4 |
| Room heating energy efficiency of composite system under moderate climatic conditions | % | 171.2 |
| Room heating energy efficiency of composite system under colder climatic conditions | % | 177.7 |
| Room heating energy efficiency of composite system under warmer climatic conditions | % | 170.2 |
| Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions | % | 6.5 |
| Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions | % | 1 |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A+++ |
| Room heating energy efficiency class of composite system under moderate climatic conditions | | A+++ |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | WPE-I 15 HK 230 Premium |
|---|----|-------------------------|
| | | 238617 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Brine |
| Low temperature heat pump | | - |
| With booster heater | | x |
| Combi boiler with heat pump | | - |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 14 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 14 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 14 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 8.32 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 12.16 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 5.05 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 7.4 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 13.77 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 3.24 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 4.75 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 8.83 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 2.23 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 2.22 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 3.92 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 13.77 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 13.77 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 13.77 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 13.77 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 13.77 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 13.77 |
| Dual mode temperature in colder climates (Tbiv) | °C | -22 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -10 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (η_s) | % | 174.2 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 168 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (η_s) | % | 166.7 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 4.24 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.4 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 4.94 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.44 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 3.26 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 5.24 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 5.03 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 3.99 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 5.44 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 5.31 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 5.16 |
| Tj = dual mode temperature in colder climates (COPd) | | 3.26 |
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 3.26 |
| Tj = dual mode temperature in warmer climates (COPd) | | 3.26 |

| | | |
|---|---|----------|
| Tj = operating temperature limit in colder climates (COPd) | | 3.26 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 3.26 |
| Tj = operating temperature limit in warmer climates (COPd) | | 3.26 |
| Operating temperature limit in moderate climates (TOL) | °C | -10.000 |
| Heating water operating temperature limit (WTOL) | °C | 75 |
| Power consumption, OFF state (Poff) | W | 19.000 |
| Power consumption, thermostat OFF state (PTO) | W | 19 |
| Standby power consumption (PSB) | W | 19.000 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 0.000 |
| Booster heater heating output in colder climates (Psup) | kW | 0 |
| Booster heater heating output (PSUB) | kW | 0 |
| Booster heater heating output in warmer climates (Psup) | kW | 0 |
| Type of energy supply, booster heater | | electric |
| Power control | | variable |
| Sound power level internal | dB(A) | 39 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 7451 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 6476 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 4211 |
| Flow rate, heat source side | m ³ /h | 1,31 |
| Energy efficiency for DHW heating (Γ_{wh}) under moderate climatic conditions | % | - |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |