



**ENERG** Y IJA  
 енергия · ενέργεια IE IA

**STIEBEL ELTRON**

WPL 07 ACS classic UK  
 compact Set S



**A+**



**A**

52 dB



- 3 kW
- 4 kW
- 3 kW

2019

811/2013

**Product datasheet: Combi heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

		<b>WPL 07 ACS classic UK compact Set S</b>
		238623
Manufacturer		STIEBEL ELTRON
Load profile		L
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Rated heating output in moderate climates for average temperature applications (Prated)	kW	4
Rated heating output in moderate climates for low temperature applications (Prated)	kW	4
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	2089
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	1769
Annual power consumption in moderate climates (AEC)	kWh/a	1535
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	116
Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )	%	166
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under moderate climatic conditions	%	109
Sound power level external	dB(A)	52
Special measures	For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions	
Rated heating output in colder climates for average temperature applications (Prated)	kW	4
Rated heating output in colder climates for low temperature applications (Prated)	kW	3
Rated heating output in warmer climates for average temperature applications (Prated)	kW	3
Rated heating output in warmer climates for low temperature applications (Prated)	kW	3
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	4016
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	2186
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	1187
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	783
Annual power consumption in colder climates (AEC)	kWh/a	1663
Annual power consumption in warmer climates (AEC)	kWh/a	1253
Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )	%	102
Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )	%	148
Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )	%	137
Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )	%	200
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under colder climatic conditions	%	101
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under warmer climatic conditions	%	134
Operation exclusively enabled during low load times		-



# ENERG

енергия · ενέργεια

Y

IJA

IE

IA

**STIEBEL ELTRON**

WPL 07 ACS classic UK compact Set S

Energy label for heating system showing a boiler icon, a radiator icon, and a tap icon. The heating system is rated A+ and the tap is rated A.

Energy scale for heating system with a radiator icon. The scale ranges from A+++ (green) to G (red). The final rating is A+.

Energy label for hot water system showing a solar panel icon, a hot water tank icon, a control panel icon, and a boiler icon. The solar panel, hot water tank, and boiler are marked with a plus sign and an empty box. The control panel is marked with a plus sign and a box containing an 'X'.

Energy scale for hot water system with a tap icon. The scale ranges from A+++ (green) to G (red). The final rating is A.

**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

		<b>WPL 07 ACS classic UK compact Set S</b>
		238623
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	116
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	120
Room heating energy efficiency of composite system under colder climatic conditions	%	109
Room heating energy efficiency of composite system under warmer climatic conditions	%	143
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	8
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	26
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A+
Energy efficiency category for DHW heating under moderate climatic conditions		A
Load profile		L

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		WPL 07 ACS classic UK compact Set S	
		238623	
Manufacturer		STIEBEL ELTRON	
Heat source		Outside air	
With booster heater		x	
Combi boiler with heat pump		-	
Rated heating output in colder climates for average temperature applications (Prated)	kW	4	
Rated heating output in moderate climates for average temperature applications (Prated)	kW	4	
Rated heating output in warmer climates for average temperature applications (Prated)	kW	3	
Tj = -7 °C heating output, partial load range in colder climates (Pdh)	kW	2.65	
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	3.10	
Tj = 2 °C heating output, partial load range in colder climates (Pdh)	kW	1.62	
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	1.60	
Tj = 2 °C heating output, partial load range in warmer climates (Pdh)	kW	3.15	
Tj = 7 °C heating output, partial load range in colder climates (Pdh)	kW	1.29	
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	1.30	
Tj = 7 °C heating output, partial load range in warmer climates (Pdh)	kW	2.03	
Tj = 12 °C heating output, partial load range in colder climates (Pdh)	kW	1.53	
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	1.50	
Tj = 12 °C heating output, partial load range in warmer climates (Pdh)	kW	1.5	
Tj = dual mode temperature in colder climates (Pdh)	kW	3	
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	2.40	
Tj = dual mode temperature in warmer climates (Pdh)	kW	3.15	
Tj = operating temperature limit in colder climates (Pdh)	kW	2.65	
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	3.10	
Tj = operating temperature limit in warmer climates (Pdh)	kW	3.15	
For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	0.00	
Dual mode temperature in colder climates (Tbiv)	°C	-10	
Dual mode temperature in moderate climates (Tbiv)	°C	-5	
Dual mode temperature in warmer climates (Tbiv)	°C	2	
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	102	
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	116	
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	137	
Tj = -7 °C COP, partial load range in colder climates (COPd)		2.3	
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2.07	
Tj = 2 °C COP, partial load range in colder climates (COPd)		3.45	
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		2.93	
Tj = 2 °C COP, partial load range in warmer climates (COPd)		2.19	
Tj = 7 °C COP, partial load range in colder climates (COPd)		4.66	
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4.13	
Tj = 7 °C COP, partial load range in warmer climates (COPd)		3.27	
Tj = 12 °C COP, partial load range in colder climates (COPd)		6.65	
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		5.97	
Tj = 12 °C COP, partial load range in warmer climates (COPd)		5.15	
Tj = dual mode temperature in colder climates (COPd)		2.09	
Tj = dual mode temperature under moderate climatic conditions (COPd)		2.17	
Tj = dual mode temperature in warmer climates (COPd)		2.19	

Tj = operating temperature limit in colder climates (COPd)		2.3
Tj = operating temperature limit under moderate climatic conditions (COPd)		2.07
Tj = operating temperature limit in warmer climates (COPd)		2.19
For air/water heat pumps: Tj= -15 °C (if TOL < -20 °C) (COPd)		0.00
Operating temperature limit in colder climates (TOL)	°C	-15
Operating temperature limit in moderate climates (TOL)	°C	-5.000
Operating temperature limit in warmer climates (TOL)	°C	2
Heating water operating temperature limit (WTOL)	°C	60
Power consumption, OFF state (Poff)	W	17.000
Power consumption, thermostat OFF state (PTO)	W	30
Standby power consumption (PSB)	W	17.000
Power consumption, operating state, with crankcase heating (PCK)	W	5.000
Booster heater heating output (PSUB)	kW	2.930
Type of energy supply, booster heater		electric
Power control		variable
Sound power level external	dB(A)	52
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	4016
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	2089
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	1187
Flow rate, heat source side	m <sup>3</sup> /h	1300
Load profile		L
Annual power consumption in colder climates (AEC)	kWh/a	1663
Annual power consumption in moderate climates (AEC)	kWh/a	1535
Annual power consumption in warmer climates (AEC)	kWh/a	1253
Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions	%	109
Special measures	For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions	