



ENERGY

STIEBEL ELTRON

HPG-I 08 DS Premium



A+++



A

46 dB



- 8 kW
- 8 kW
- 8 kW

2019

811/2013

Product datasheet: Combi heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)


| | | HPG-I 08 DS Premium |
|---|-------|---|
| | | 202624 |
| Manufacturer | | STIEBEL ELTRON |
| Load profile | | XL |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A+++ |
| Energy efficiency class for central heating in moderate climates for low temperature applications | | A+++ |
| Energy efficiency category for DHW heating under moderate climatic conditions | | A |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 7 |
| Rated heating output in moderate climates for low temperature applications (Prated) | kW | 8 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 3461 |
| Annual energy consumption in moderate climates for low temperature applications (QHE) | kWh/a | 3094 |
| Annual power consumption in moderate climates (AEC) | kWh/a | 1556 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 158 |
| Seasonal room heating efficiency in moderate climates for low temperature applications (η_s) | % | 197 |
| Energy efficiency for DHW heating (η_{wh}) under moderate climatic conditions | % | 108 |
| Sound power level internal | dB(A) | 46 |
| Special measures | | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 7 |
| Rated heating output in colder climates for low temperature applications (Prated) | kW | 8 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 7 |
| Rated heating output in warmer climates for low temperature applications (Prated) | kW | 8 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 3985 |
| Annual energy consumption in colder climates for low temperature applications (QHE) | kWh/a | 3570 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 2243 |
| Annual energy consumption in warmer climates for low temperature applications (QHE) | kWh/a | 1997 |
| Annual power consumption in colder climates (AEC) | kWh/a | 1556 |
| Annual power consumption in warmer climates (AEC) | kWh/a | 1556 |
| Seasonal room heating efficiency in colder climates for average temperature applications (η_s) | % | 163.4 |
| Seasonal room heating efficiency in colder climates for low temperature applications (η_s) | % | 203.7 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (η_s) | % | 157.1 |
| Seasonal room heating efficiency in warmer climates for low temperature applications (η_s) | % | 197.1 |
| Energy efficiency for DHW heating (η_{wh}) under colder climatic conditions | % | 108 |
| Energy efficiency for DHW heating (η_{wh}) under warmer climatic conditions | % | 108 |
| Operation exclusively enabled during low load times | | - |



ENERGY

STIEBEL ELTRON


HPG-I 08 DS Premium



A+++



A



A+++

A++

A+

A

B

C

D

E

F

G

A+++

+



+



+



+



A+++

A++

A+

A

B

C

D

E

F

G

A

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)

| | | HPG-I 08 DS Premium |
|---|---|----------------------------|
| | | 202624 |
| Manufacturer | | STIEBEL ELTRON |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 158 |
| Contribution of temperature controller to room heating energy efficiency | % | 4 |
| Room heating energy efficiency of composite system under moderate climatic conditions | % | 161 |
| Room heating energy efficiency of composite system under colder climatic conditions | % | 166.9 |
| Room heating energy efficiency of composite system under warmer climatic conditions | % | 160.6 |
| Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions | % | 6 |
| Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions | % | 0.4 |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A+++ |
| Room heating energy efficiency class of composite system under moderate climatic conditions | | A+++ |
| Energy efficiency category for DHW heating under moderate climatic conditions | | A |
| Load profile | | XL |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | HPG-I 08 DS Premium |
|---|----|---------------------|
| | | 202624 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Brine |
| Low temperature heat pump | | - |
| With booster heater | | x |
| Combi boiler with heat pump | | x |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 7 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 7 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 7 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 4.18 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 6.12 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 2.54 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 3.72 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 6.93 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 1.63 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 2.39 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 4.45 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 1.09 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 1.08 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 1.97 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 6.93 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 6.93 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 6.93 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 6.93 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 6.93 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 6.93 |
| Dual mode temperature in colder climates (Tbiv) | °C | -22 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -10 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | 163.4 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | 158 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | 157.1 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 4.07 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.44 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 4.6 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.21 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 3.22 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 4.9 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.69 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 3.88 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 4.75 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.61 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 4.85 |
| Tj = dual mode temperature in colder climates (COPd) | | 3.22 |
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 3.22 |
| Tj = dual mode temperature in warmer climates (COPd) | | 3.22 |

| | | |
|---|---|----------|
| T _j = operating temperature limit in colder climates (COP _d) | | 3.22 |
| T _j = operating temperature limit under moderate climatic conditions (COP _d) | | 3.22 |
| T _j = operating temperature limit in warmer climates (COP _d) | | 3.22 |
| Operating temperature limit in moderate climates (TOL) | °C | -10.000 |
| Heating water operating temperature limit (WTOL) | °C | 75 |
| Power consumption, OFF state (P _{off}) | W | 16.000 |
| Power consumption, thermostat OFF state (PTO) | W | 16 |
| Standby power consumption (PSB) | W | 16.000 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 0.000 |
| Booster heater heating output in colder climates (P _{sup}) | kW | 0 |
| Booster heater heating output (P _{SUB}) | kW | 0 |
| Booster heater heating output in warmer climates (P _{sup}) | kW | 0 |
| Type of energy supply, booster heater | | electric |
| Power control | | variable |
| Sound power level internal | dB(A) | 46 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 3985 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 3461 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 2243 |
| Flow rate, heat source side | m ³ /h | 0.68 |
| Load profile | | XL |
| Daily power consumption in colder climates (QELEC) | kWh | 7.08 |
| Daily power consumption (Qelec) | kWh | 7.08 |
| Daily power consumption in warmer climates (QELEC) | kWh | 7.08 |
| Annual power consumption in colder climates (AEC) | kWh/a | 1556 |
| Annual power consumption in moderate climates (AEC) | kWh/a | 1556 |
| Annual power consumption in warmer climates (AEC) | kWh/a | 1556 |
| Energy efficiency for DHW heating (Γ _{wh}) under moderate climatic conditions | % | 108 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |