



ENERGY

STIEBEL ELTRON WPF 27 HT



55 °C

35 °C



64 dB

64 dB

| | |
|------|------|
| ■ 32 | ■ 34 |
| ■ 25 | ■ 27 |
| ■ 25 | ■ 27 |
| kW | kW |

2019

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)

| | | WPF 27 HT |
|---|---|------------------|
| | | 233009 |
| Manufacturer | | STIEBEL ELTRON |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A++ |
| Energy efficiency class for central heating in moderate climates for low temperature applications | | A+++ |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 25 |
| Rated heating output in moderate climates for low temperature applications (Prated) | kW | 27 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 131 |
| Seasonal room heating efficiency in moderate climates for low temperature applications (η_s) | % | 175 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 14872 |
| Annual energy consumption in moderate climates for low temperature applications (QHE) | kWh/a | 12359 |
| Sound power level internal | dB(A) | 64 |
| Sound power level external | dB(A) | 64 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 32 |
| Rated heating output in colder climates for low temperature applications (Prated) | kW | 34 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 25 |
| Rated heating output in warmer climates for low temperature applications (Prated) | kW | 27 |
| Seasonal room heating efficiency in colder climates for average temperature applications (η_s) | % | 136 |
| Seasonal room heating efficiency in colder climates for low temperature applications (η_s) | % | 180 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (η_s) | % | 131 |
| Seasonal room heating efficiency in warmer climates for low temperature applications (η_s) | % | 174 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 21670 |
| Annual energy consumption in colder climates for low temperature applications (QHE) | kWh/a | 17849 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 9675 |
| Annual energy consumption in warmer climates for low temperature applications (QHE) | kWh/a | 8031 |



ENERGY

STIEBEL ELTRON

WPF 27 HT



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

+



+



+



+



Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)

| | | WPF 27 HT |
|---|---|------------------|
| | | 233009 |
| Manufacturer | | STIEBEL ELTRON |
| Seasonal room heating efficiency in moderate climates for average temperature applications (η_s) | % | 131 |
| Temperature controller class | | VII |
| Contribution of temperature controller to room heating energy efficiency | % | 3.50 |
| Room heating energy efficiency of composite system under moderate climatic conditions | % | 135 |
| Room heating energy efficiency of composite system under colder climatic conditions | % | 140 |
| Room heating energy efficiency of composite system under warmer climatic conditions | % | 135 |
| Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions | % | 5 |
| Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions | % | 0 |
| Energy efficiency class for central heating in moderate climates for medium temperature applications | | A++ |
| Room heating energy efficiency class of composite system under moderate climatic conditions | | A++ |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

| | | WPF 27 HT |
|---|----|----------------|
| | | 233009 |
| Manufacturer | | STIEBEL ELTRON |
| Heat source | | Brine |
| With booster heater | | - |
| Combi boiler with heat pump | | - |
| Rated heating output in colder climates for average temperature applications (Prated) | kW | 32 |
| Rated heating output in moderate climates for average temperature applications (Prated) | kW | 25 |
| Rated heating output in warmer climates for average temperature applications (Prated) | kW | 25 |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh) | kW | 26.1 |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 25.30 |
| Tj = -7 °C heating output, partial load range in warmer climates (Pdh) | kW | 25.1 |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh) | kW | 26.6 |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 26.10 |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh) | kW | 25.1 |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh) | kW | 27 |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 26.60 |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh) | kW | 25.8 |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh) | kW | 27.3 |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh) | kW | 27.10 |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh) | kW | 26.8 |
| Tj = dual mode temperature in colder climates (Pdh) | kW | 25.8 |
| Tj = dual mode temperature under moderate climatic conditions (Pdh) | kW | 25.10 |
| Tj = dual mode temperature in warmer climates (Pdh) | kW | 25.1 |
| Tj = operating temperature limit in colder climates (Pdh) | kW | 25.1 |
| Tj = operating temperature limit under moderate climatic conditions (Pdh) | kW | 25.10 |
| Tj = operating temperature limit in warmer climates (Pdh) | kW | 25.1 |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh) | kW | 25.10 |
| Dual mode temperature in colder climates (Tbiv) | °C | -15 |
| Dual mode temperature in moderate climates (Tbiv) | °C | -10 |
| Dual mode temperature in warmer climates (Tbiv) | °C | 2 |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs) | % | 136 |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | % | 131 |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs) | % | 131 |
| Tj = -7 °C COP, partial load range in colder climates (COPd) | | 3.46 |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.06 |
| Tj = -7 °C COP, partial load range in warmer climates (COPd) | | 2.96 |
| Tj = 2 °C COP, partial load range in colder climates (COPd) | | 3.77 |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.48 |
| Tj = 2 °C COP, partial load range in warmer climates (COPd) | | 2.96 |
| Tj = 7 °C COP, partial load range in colder climates (COPd) | | 4.05 |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd) | | 3.78 |
| Tj = 7 °C COP, partial load range in warmer climates (COPd) | | 3.29 |
| Tj = 12 °C COP, partial load range in colder climates (COPd) | | 4.28 |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd) | | 4.12 |
| Tj = 12 °C COP, partial load range in warmer climates (COPd) | | 3.89 |
| Tj = dual mode temperature in colder climates (COPd) | | 3.29 |

| | | |
|---|---|----------|
| Tj = dual mode temperature under moderate climatic conditions (COPd) | | 2.96 |
| Tj = dual mode temperature in warmer climates (COPd) | | 2.96 |
| Tj = operating temperature limit in colder climates (COPd) | | 2.96 |
| Tj = operating temperature limit under moderate climatic conditions (COPd) | | 2.96 |
| Tj = operating temperature limit in warmer climates (COPd) | | 2.96 |
| For air/water heat pumps: Tj= -15 °C (if TOL < -20 °C) (COPd) | | 2.96 |
| Heating water operating temperature limit (WTOL) | °C | 75 |
| Power consumption, OFF state (Poff) | W | 0.000 |
| Power consumption, thermostat OFF state (PTO) | W | 3 |
| Standby power consumption (PSB) | W | 3.000 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 46.000 |
| Booster heater heating output (PSUB) | kW | 0.000 |
| Type of energy supply, booster heater | | electric |
| Power control | | Fixed |
| Sound power level external | dB(A) | 64 |
| Sound power level internal | dB(A) | 64 |
| Annual energy consumption in colder climates for average temperature applications (QHE) | kWh/a | 21670 |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a | 14872 |
| Annual energy consumption in warmer climates for average temperature applications (QHE) | kWh/a | 9675 |
| Flow rate, heat source side | m ³ /h | 6.75 |
| Special measures | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions | |