



# ENERGY

**STIEBEL ELTRON**

HPA-O 3 CS Plus  
compact Set S



**A+**



**A**

Two icons showing sound power level: a house with a speaker icon and a house with a speaker icon and the text "52 dB".



Legend for power output: a dark blue square for 3 kW, a medium blue square for 4 kW, and a light blue square for 3 kW.

2019

811/2013

**Product datasheet: Combi heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**


		<b>HPA-O 3 CS Plus compact Set S</b>
		238992
Manufacturer		STIEBEL ELTRON
Load profile		L
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Rated heating output in moderate climates for average temperature applications (Prated)	kW	3
Rated heating output in moderate climates for low temperature applications (Prated)	kW	4
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	2089
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	1769
Annual power consumption in moderate climates (AEC)	kWh/a	905
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	113
Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )	%	166
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under moderate climatic conditions	%	113
Sound power level external	dB(A)	52
Special measures	For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions	
Rated heating output in colder climates for average temperature applications (Prated)	kW	4
Rated heating output in colder climates for low temperature applications (Prated)	kW	3
Rated heating output in warmer climates for average temperature applications (Prated)	kW	3
Rated heating output in warmer climates for low temperature applications (Prated)	kW	3
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	4016
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	2186
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	1187
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	783
Annual power consumption in colder climates (AEC)	kWh/a	949
Annual power consumption in warmer climates (AEC)	kWh/a	717
Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )	%	105
Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )	%	150
Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )	%	139
Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )	%	204
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under colder climatic conditions	%	102
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under warmer climatic conditions	%	139




# ENERGY

**STIEBEL ELTRON**

HPA-O 3 CS Plus compact Set S




Energy label for heating system: A+ for heating, A for hot water.



Energy label for heating system: A+ for heating, A+ for hot water.

Energy label for hot water system: + Solar, + Tank, + Control, + Heating.



Energy label for hot water system: A for hot water.

**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

		<b>HPA-O 3 CS Plus compact Set S</b>
		238992
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	113
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	117
Room heating energy efficiency of composite system under colder climatic conditions	%	109
Room heating energy efficiency of composite system under warmer climatic conditions	%	143
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	8
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	26
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A+
Energy efficiency category for DHW heating under moderate climatic conditions		A
Load profile		L

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		HPA-O 3 CS Plus compact Set S	
		238992	
Manufacturer		STIEBEL ELTRON	
Heat source		Outside air	
Low temperature heat pump			-
With booster heater			x
Combi boiler with heat pump			x
Rated heating output in colder climates for average temperature applications (Prated)	kW		4
Rated heating output in moderate climates for average temperature applications (Prated)	kW		3
Rated heating output in warmer climates for average temperature applications (Prated)	kW		3
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		3.1
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		1.6
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		1.3
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW		1.5
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW		2.4
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW		3.1
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW		0
Dual mode temperature in moderate climates (Tbiv)	°C		-5
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%		105
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%		113
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%		139
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)			2.07
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)			2.93
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)			4.13
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)			5.97
Tj = dual mode temperature under moderate climatic conditions (COPd)			2.17
Tj = operating temperature limit under moderate climatic conditions (COPd)			2.07
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)			0
Operating temperature limit in moderate climates (TOL)	°C		-7
Heating water operating temperature limit (WTOL)	°C		60
Power consumption, OFF state (Poff)	W		17
Power consumption, thermostat OFF state (PTO)	W		30
Standby power consumption (PSB)	W		17
Power consumption, operating state, with crankcase heating (PCK)	W		5
Booster heater heating output (PSUB)	kW		2.93
Type of energy supply, booster heater			electric
Power control			variable
Sound power level external	dB(A)		52
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a		4016
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a		2089
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a		1187
Flow rate, heat source side	m <sup>3</sup> /h		1300
Load profile			L
Annual power consumption in colder climates (AEC)	kWh/a		949

Annual power consumption in moderate climates (AEC)	kWh/a	905
Annual power consumption in warmer climates (AEC)	kWh/a	717
Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions	%	113

Special measures

For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions