



**ENERG**  
енергия · ενεργεια



WPL-S 25 HK 400 Premium

**STIEBEL ELTRON**



55 °C

35 °C



**A<sup>++</sup>**

**A<sup>++</sup>**



**56** dB



**64** dB

■ 26

■ 29

■ 27

kW

■ 25

■ 29

■ 28

kW



2019

811/2013

Технические характеристики изделия:

|              |       | WPL-S 25 HK 400 Premium |
|--------------|-------|-------------------------|
|              |       | 202800                  |
| Manufacturer |       | STIEBEL ELTRON          |
|              |       | A++                     |
|              |       | A++                     |
|              | kW    | 29                      |
|              | kW    | 29                      |
|              | %     | 134                     |
|              | %     | 150                     |
|              | kWh/a | 17450                   |
|              | kWh/a | 15634                   |
|              | dB(A) | 56                      |
|              | kW    | 26                      |
|              | kW    | 25                      |
|              | kW    | 27                      |
|              | kW    | 28                      |
|              | %     | 124                     |
|              | %     | 137                     |
|              | %     | 150                     |
|              | %     | 168                     |
|              | kWh/a | 20254                   |
|              | kWh/a | 17575                   |
|              | kWh/a | 9406                    |
|              | kWh/a | 8891                    |
|              | dB(A) | 64                      |



ENERG  
енергия · ενεργεια



WPL-S 25 HK 400 Premium

**STIEBEL ELTRON**



**A<sup>++</sup>**

**A<sup>+++</sup>**

**A<sup>++</sup>**

**A<sup>++</sup>**

**A<sup>+</sup>**

**A**

**B**

**C**

**D**

**E**

**F**

**G**

+



+



+



+



Технические характеристики изделия:

|              |   | WPL-S 25 HK 400 Premium |
|--------------|---|-------------------------|
|              |   | 202800                  |
| Manufacturer |   | STIEBEL ELTRON          |
|              | % | 150                     |
|              |   | VII                     |
|              | % | 4                       |
|              | % | 134                     |
|              | % | 124                     |
|              | % | 150                     |
|              | % | 16                      |
|              | % | 22                      |
|              |   | A++                     |
|              |   | A++                     |

Технические характеристики изделия:

|              |    | WPL-S 25 HK 400 Premium |
|--------------|----|-------------------------|
|              |    | 202800                  |
| Manufacturer |    | STIEBEL ELTRON          |
|              |    | Außenluft               |
|              |    | -                       |
|              |    | -                       |
|              |    | -                       |
|              | kW | 26                      |
|              | kW | 29                      |
|              | kW | 27                      |
|              | kW | 27,1                    |
|              | kW | 26,0                    |
|              | kW | 29,6                    |
|              | kW | 29,0                    |
|              | kW | 27,0                    |
|              | kW | 38,5                    |
|              | kW | 38,0                    |
|              | kW | 35,0                    |
|              | kW | 41,3                    |
|              | kW | 41,0                    |
|              | kW | 40,5                    |
|              | kW | 22,0                    |
|              | kW | 26,0                    |
|              | kW | 27,0                    |
|              | kW | 16,8                    |
|              | kW | 24,5                    |
|              | kW | 27,0                    |
|              | °C | -15                     |
|              | °C | -7                      |
|              | °C | 2                       |
|              | %  | 124                     |
|              | %  | 134                     |
|              | %  | 150                     |
|              |    | 2,80                    |
|              |    | 2,60                    |
|              |    | 3,60                    |
|              |    | 3,40                    |
|              |    | 2,60                    |
|              |    | 4,20                    |
|              |    | 4,00                    |
|              |    | 3,60                    |
|              |    | 4,70                    |
|              |    | 460,00                  |
|              |    | 4,40                    |
|              |    | 2,30                    |
|              |    | 2,60                    |
|              |    | 2,60                    |
|              |    | 1,60                    |
|              |    | 2,40                    |
|              |    | 2,60                    |
|              | °C | -22                     |
|              | °C | 2                       |
|              | °C | 65                      |
|              | °C | 65                      |
|              | °C | 65                      |
|              | W  | 25                      |
|              | W  | 25                      |
|              | W  | 25                      |

|  |       |            |
|--|-------|------------|
|  | W     | 0          |
|  |       | elektrisch |
|  |       | fest       |
|  | dB(A) | 64         |
|  | dB(A) | 56         |
|  | kWh/a | 20254      |
|  | kWh/a | 17450      |
|  | kWh/a | 9406       |
|  | m³/h  | 9800       |