



ENERG  
енергия · ενεργεια



tecalor

TTF 6.6



55 °C

35 °C



A+++

A+++



41 dB



0 dB

6  
6  
6

kW

7  
7  
7

kW



2019

811/2013

|  |       | TTF 6.6 |
|--|-------|---------|
|  |       | 190603  |
| Manufacturer   |       | tecalor |
| Space heating energy efficiency class under average climate conditions, medium-temperature applications                    |       | A+++    |
| Energy efficiency class, space heating under average climate conditions, low-temperature applications                      |       | A+++    |
| Rated heating output under average climate conditions for medium-temperature applications (P rated)                        | kW    | 6       |
| Rated heating output under average climate conditions for low-temperature applications (P rated)                           | kW    | 7       |
| Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications ( $\eta_s$ ) | %     | 159     |
| Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )    | %     | 200     |
| Annual energy consumption under average climate conditions for medium-temperature applications (QHE)                       | kWh/a | 2988    |
| Annual energy consumption under average climate conditions for low-temperature applications (QHE)                          | kWh/a | 2662    |
| Sound power level, indoor  | dB(A) | 41      |
| Option for operation only at off-peak times  |       | -       |
| Rated heating output under colder climate conditions for medium-temperature applications (P rated)                         | kW    | 6       |
| Rated heating output under colder climate conditions for low-temperature applications (P rated)                            | kW    | 7       |
| Rated heating output under warmer climate conditions for medium-temperature applications (P rated)                         | kW    | 6       |
| Rated heating output under warmer climate conditions for low-temperature applications (P rated)                            | kW    | 7       |
| Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications ( $\eta_s$ )  | %     | 166     |
| Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications ( $\eta_s$ )     | %     | 207     |
| Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications ( $\eta_s$ )  | %     | 158     |
| Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications ( $\eta_s$ )     | %     | 198     |
| Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)                        | kWh/a | 3439    |
| Annual energy consumption under colder climate conditions for low-temperature applications (QHE)                           | kWh/a | 3069    |
| Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)                        | kWh/a | 1954    |
| Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)                           | kWh/a | 1741    |
| Sound power level, outdoor   | dB(A) | 0       |



ENERG  
енергия · ενέργεια



tecalor

TTF 6.6



A<sup>+++</sup>

A<sup>+++</sup>

A<sup>++</sup>

A<sup>+</sup>

A

B

C

D


E

F

G

A<sup>+++</sup>

+



+



+



+



Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

|   |   |         |
|---|---|---------|
|   |   | TTF 6.6 |
|   |   | 190603  |
| Manufacturer  |   | tecalor |
| Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )                 | % | 200     |
| Temperature control class   |   | VII     |
| Contribution of temperature control to space heating energy efficiency  | % | 4       |
| Space heating energy efficiency of package under average climate conditions   | % | 163     |
| Space heating energy efficiency of package under colder climate conditions  | % | 169     |
| Space heating energy efficiency of package under warmer climate conditions  | % | 161     |
| Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions | % | 6       |
| Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions | % | 2       |
| Energy efficiency class, space heating under average climate conditions, low-temperature applications                                   |   | A+++    |
| Space heating energy efficiency class of package under average climate conditions   |   | A+++    |

**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

|  |    | <b>TTF 6.6</b> |
|--|----|----------------|
|  |    | 190603         |
| Manufacturer   |    | tecalor        |
| Heat source  |    | Sole           |
| Low temperature heat pump  |    | -              |
| With auxiliary heater  |    | x              |
| Combination heater with heat pump  |    | -              |
| Rated heating output under colder climate conditions for medium-temperature applications (P rated)                 | kW | 6              |
| Rated heating output under average climate conditions for medium-temperature applications (P rated)                | kW | 6              |
| Rated heating output under warmer climate conditions for medium-temperature applications (P rated)                 | kW | 6              |
| Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)                                | kW | 3,7            |
| Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)                               | kW | 5,3            |
| Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)                                 | kW | 2,2            |
| Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)                                | kW | 3,3            |
| Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)                                 | kW | 6,1            |
| Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)                                 | kW | 1,4            |
| Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)                                | kW | 2,1            |
| Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)                                 | kW | 3,9            |
| Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)                                | kW | 1,1            |
| Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)                               | kW | 1,1            |
| Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)                                | kW | 1,7            |
| Tj = dual mode temperature under colder climate conditions (Pdh)   | kW | 6,1            |
| Tj = dual mode temperature under average climate conditions (Pdh)  | kW | 6,1            |
| Tj = dual mode temperature under warmer climate conditions (Pdh)   | kW | 6,1            |
| Tj = operating temperature limit under colder climate conditions (Pdh)   | kW | 6,1            |
| Tj = operating temperature limit under average climate conditions (Pdh)  | kW | 6,1            |
| Tj = operating temperature limit under warmer climate conditions (Pdh)   | kW | 6,1            |
| Dual mode temperature under colder climate conditions (Tbiv)   | °C | -22            |
| Dual mode temperature under average climate conditions (Tbiv)  | °C | -10            |
| Dual mode temperature under warmer climate conditions (Tbiv)   | °C | 2              |
| Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)  | %  | 166            |
| Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs) | %  | 159            |
| Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)  | %  | 158            |
| Tj = -7 °C COP, partial load range under colder climate conditions (COPd)  |    | 4,15           |
| Tj = -7 °C COP, partial load range under average climate conditions (COPd)   |    | 3,55           |
| Tj = 2 °C COP, partial load range under colder climate conditions (COPd)   |    | 4,68           |
| Tj = 2 °C COP, partial load range under average climate conditions (COPd)  |    | 4,27           |
| Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)   |    | 3,34           |
| Tj = 7 °C COP, partial load range under colder climate conditions (COPd)   |    | 4,80           |
| Tj = 7 °C COP, partial load range under average climate conditions (COPd)  |    | 4,76           |
| Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)   |    | 3,97           |

|  |       |              |
|--|-------|--------------|
| Tj = 12 °C COP, partial load range under colder climate conditions (COPd)                            |       | 4,73         |
| Tj = 12 °C COP, partial load range under average climate conditions (COPd)                           |       | 4,61         |
| Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)                            |       | 4,81         |
| Tj = dual mode temperature under colder climate conditions (COPd)                                    |       | 3,34         |
| Tj = dual mode temperature under average climate conditions (COPd)                                   |       | 3,34         |
| Tj = dual mode temperature under warmer climate conditions (COPd)                                    |       | 3,34         |
| Tj = operating temperature limit under colder climate conditions (COPd)                              |       | 3,34         |
| Tj = operating temperature limit under average climate conditions (COPd)                             |       | 3,34         |
| Tj = operating temperature limit under warmer climate conditions (COPd)                              |       | 3,34         |
| Operating temperature limit under colder climate conditions (TOL)                                    | °C    | -22          |
| Operating temperature limit under average climate conditions (TOL)                                   | °C    | -10          |
| Operating temperature limit under warmer climate conditions (TOL)                                    | °C    | 2            |
| Operating temperature limit of heating water under colder climate conditions (WTOL)                  | °C    | 75           |
| Operating temperature limit of heating water under average climate conditions (WTOL)                 | °C    | 75           |
| Operating temperature limit of heating water under warmer climate conditions (WTOL)                  | °C    | 75           |
| Power consumption, off-mode (Poff)   | W     | 16           |
| Power consumption, thermostat off-mode (PTO)   | W     | 16           |
| Power consumption, standby state (PSB)   | W     | 16           |
| Power consumption, operating state, with crankcase heating (PCK)                                     | W     | 0            |
| Rated heating output of auxiliary heater under colder climate conditions (PSUP)                      | kW    | 0,0          |
| Rated heating output of auxiliary heater under average climate conditions (PSUP)                     | kW    | 0,0          |
| Rated heating output of auxiliary heater under warmer climate conditions (PSUP)                      | kW    | 0,0          |
| Type of energy supply, auxiliary heater  |       | elektrisch   |
| Output control   |       | veränderlich |
| Sound power level, outdoor   | dB(A) | 0            |
| Sound power level, indoor  | dB(A) | 41           |
| Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)  | kWh/a | 3439         |
| Annual energy consumption under average climate conditions for medium-temperature applications (QHE) | kWh/a | 2988         |
| Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)  | kWh/a | 1954         |
| Flow rate on heat source side  | m³/h  | 6            |