



# ENERGY

## tecalor

TTF 35



55 °C

35 °C



A<sup>++</sup>

A<sup>+++</sup>



60 dB



60 dB

■ 43

■ 34

■ 34

kW

■ 47

■ 38

■ 38

kW



2019

811/2013

		TTF 35
		190365
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	34
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	38
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications ( $\eta_s$ )	%	133
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )	%	200
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	20029
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	15136
Sound power level, indoor	dB(A)	60
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	43
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	47
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	34
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	38
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications ( $\eta_s$ )	%	139
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications ( $\eta_s$ )	%	208
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications ( $\eta_s$ )	%	132
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications ( $\eta_s$ )	%	199
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	28986
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	21594
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	13033
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	9834
Sound power level, outdoor	dB(A)	60



# ENERGY

tecalor

TTF 35



A<sup>++</sup>

A<sup>+++</sup>

A<sup>++</sup>

A<sup>++</sup>

A<sup>+</sup>

A

B

C


D

E

F

G

+



+



+



+



**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

		<b>TTF 35</b>
		190365
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )	%	200
Temperature control class		VII
Contribution of temperature control to space heating energy efficiency	%	4
Space heating energy efficiency of package under average climate conditions	%	137
Space heating energy efficiency of package under colder climate conditions	%	143
Space heating energy efficiency of package under warmer climate conditions	%	136
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	6
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	1
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A++

**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

		<b>TTF 35</b>
		190365
Manufacturer		tecalor
Heat source		Sole
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	43
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	34
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	34
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	35,8
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	34,5
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	36,7
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	35,8
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	34,1
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	37,4
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	36,7
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	35,2
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	37,9
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	37,5
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	37,0
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	35,3
Tj = dual mode temperature under average climate conditions (Pdh)	kW	34,1
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	34,1
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	34,1
Tj = operating temperature limit under average climate conditions (Pdh)	kW	34,1
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	34,1
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	34,1
Dual mode temperature under colder climate conditions (Tbiv)	°C	-15
Dual mode temperature under average climate conditions (Tbiv)	°C	-10
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	139
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	133
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	132
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		3,48
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		2,95
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		3,91
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		3,50
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,82
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		4,32
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		3,91
Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,24

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		4,66
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		442,00
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		4,08
Tj = dual mode temperature under colder climate conditions (COPd)		3,25
Tj = dual mode temperature under average climate conditions (COPd)		2,82
Tj = dual mode temperature under warmer climate conditions (COPd)		2,82
Tj = operating temperature limit under colder climate conditions (COPd)		2,82
Tj = operating temperature limit under average climate conditions (COPd)		2,82
Tj = operating temperature limit under warmer climate conditions (COPd)		2,82
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		2,82
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	60
Power consumption, off-mode (Poff)	W	0
Power consumption, thermostat off-mode (PTO)	W	7
Power consumption, standby state (PSB)	W	7
Power consumption, operating state, with crankcase heating (PCK)	W	74
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	0,0
Type of energy supply, auxiliary heater		elektrisch
Output control		fest
Sound power level, outdoor	dB(A)	60
Sound power level, indoor	dB(A)	60
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	28986
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	20029
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	13033
Flow rate on heat source side	m <sup>3</sup> /h	88