



ENERGY

tecalor

TTF 27 HT



55 °C

35 °C



A⁺⁺


A⁺⁺⁺



64 dB



64 dB



2019

811/2013

| | | TTF 27 HT |
|----------------------------------------------------------------------------------------------------------------------------|-------|-----------|
| | | 190369 |
| Manufacturer | | tecalor |
| Space heating energy efficiency class under average climate conditions, medium-temperature applications | | A++ |
| Energy efficiency class, space heating under average climate conditions, low-temperature applications | | A+++ |
| Rated heating output under average climate conditions for medium-temperature applications (P rated) | kW | 25 |
| Rated heating output under average climate conditions for low-temperature applications (P rated) | kW | 27 |
| Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s) | % | 131 |
| Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s) | % | 175 |
| Annual energy consumption under average climate conditions for medium-temperature applications (QHE) | kWh/a | 14872 |
| Annual energy consumption under average climate conditions for low-temperature applications (QHE) | kWh/a | 12359 |
| Sound power level, indoor | dB(A) | 64 |
| Rated heating output under colder climate conditions for medium-temperature applications (P rated) | kW | 32 |
| Rated heating output under colder climate conditions for low-temperature applications (P rated) | kW | 34 |
| Rated heating output under warmer climate conditions for medium-temperature applications (P rated) | kW | 25 |
| Rated heating output under warmer climate conditions for low-temperature applications (P rated) | kW | 27 |
| Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s) | % | 136 |
| Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s) | % | 180 |
| Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s) | % | 131 |
| Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s) | % | 174 |
| Annual energy consumption under colder climate conditions for medium-temperature applications (QHE) | kWh/a | 21670 |
| Annual energy consumption under colder climate conditions for low-temperature applications (QHE) | kWh/a | 17849 |
| Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE) | kWh/a | 9675 |
| Annual energy consumption under warmer climate conditions for low-temperature applications (QHE) | kWh/a | 8031 |
| Sound power level, outdoor | dB(A) | 64 |






ENERGY


tecalor


TTF 27 HT




+ 

+ 

+ 

+ 













Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

| | | TTF 27 HT |
|-----------------------------------------------------------------------------------------------------------------------------------------|---|------------------|
| | | 190369 |
| Manufacturer | | tecalor |
| Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s) | % | 175 |
| Temperature control class | | VII |
| Contribution of temperature control to space heating energy efficiency | % | 4 |
| Space heating energy efficiency of package under average climate conditions | % | 135 |
| Space heating energy efficiency of package under colder climate conditions | % | 140 |
| Space heating energy efficiency of package under warmer climate conditions | % | 135 |
| Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions | % | 5 |
| Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions | % | 0 |
| Energy efficiency class, space heating under average climate conditions, low-temperature applications | | A+++ |
| Space heating energy efficiency class of package under average climate conditions | | A++ |

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

| | | TTF 27 HT |
|--------------------------------------------------------------------------------------------------------------------|----|------------------|
| | | 190369 |
| Manufacturer | | tecalor |
| Heat source | | Sole |
| With auxiliary heater | | - |
| Combination heater with heat pump | | - |
| Rated heating output under colder climate conditions for medium-temperature applications (P rated) | kW | 32 |
| Rated heating output under average climate conditions for medium-temperature applications (P rated) | kW | 25 |
| Rated heating output under warmer climate conditions for medium-temperature applications (P rated) | kW | 25 |
| Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 26,1 |
| Tj = -7 °C heating output, partial load range under average climate conditions (Pdh) | kW | 25,3 |
| Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 26,6 |
| Tj = 2 °C heating output, partial load range under average climate conditions (Pdh) | kW | 26,1 |
| Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh) | kW | 25,1 |
| Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 27,0 |
| Tj = 7 °C heating output, partial load range under average climate conditions (Pdh) | kW | 26,6 |
| Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh) | kW | 25,8 |
| Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 27,3 |
| Tj = 12 °C heating output, partial load range under average climate conditions (Pdh) | kW | 27,1 |
| Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh) | kW | 26,8 |
| Tj = dual mode temperature under colder climate conditions (Pdh) | kW | 25,8 |
| Tj = dual mode temperature under average climate conditions (Pdh) | kW | 25,1 |
| Tj = dual mode temperature under warmer climate conditions (Pdh) | kW | 25,1 |
| Tj = operating temperature limit under colder climate conditions (Pdh) | kW | 25,1 |
| Tj = operating temperature limit under average climate conditions (Pdh) | kW | 25,1 |
| Tj = operating temperature limit under warmer climate conditions (Pdh) | kW | 25,1 |
| For air source heat pumps: Tj = -15 °C (if TOL< -20 °C) (Pdh) | kW | 25,1 |
| Dual mode temperature under colder climate conditions (Tbiv) | °C | -15 |
| Dual mode temperature under average climate conditions (Tbiv) | °C | -10 |
| Dual mode temperature under warmer climate conditions (Tbiv) | °C | 2 |
| Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs) | % | 136 |
| Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs) | % | 131 |
| Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs) | % | 131 |
| Tj = -7 °C COP, partial load range under colder climate conditions (COPd) | | 3,46 |
| Tj = -7 °C COP, partial load range under average climate conditions (COPd) | | 3,06 |
| Tj = 2 °C COP, partial load range under colder climate conditions (COPd) | | 3,77 |
| Tj = 2 °C COP, partial load range under average climate conditions (COPd) | | 3,48 |
| Tj = 2 °C COP, partial load range under warmer climate conditions (COPd) | | 2,96 |
| Tj = 7 °C COP, partial load range under colder climate conditions (COPd) | | 4,05 |
| Tj = 7 °C COP, partial load range under average climate conditions (COPd) | | 3,78 |
| Tj = 7 °C COP, partial load range under warmer climate conditions (COPd) | | 3,29 |

| | | |
|------------------------------------------------------------------------------------------------------|-------|------------|
| Tj = 12 °C COP, partial load range under colder climate conditions (COPd) | | 4,28 |
| Tj = 12 °C COP, partial load range under average climate conditions (COPd) | | 412,00 |
| Tj = 12 °C COP, partial load range under warmer climate conditions (COPd) | | 3,89 |
| Tj = dual mode temperature under colder climate conditions (COPd) | | 3,29 |
| Tj = dual mode temperature under average climate conditions (COPd) | | 2,96 |
| Tj = dual mode temperature under warmer climate conditions (COPd) | | 2,96 |
| Tj = operating temperature limit under colder climate conditions (COPd) | | 2,96 |
| Tj = operating temperature limit under average climate conditions (COPd) | | 2,96 |
| Tj = operating temperature limit under warmer climate conditions (COPd) | | 2,96 |
| For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd) | | 2,96 |
| Operating temperature limit of heating water under average climate conditions (WTOL) | °C | 75 |
| Power consumption, off-mode (Poff) | W | 0 |
| Power consumption, thermostat off-mode (PTO) | W | 3 |
| Power consumption, standby state (PSB) | W | 3 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 46 |
| Rated heating output of auxiliary heater under average climate conditions (PSUP) | kW | 0,0 |
| Type of energy supply, auxiliary heater | | elektrisch |
| Output control | | fest |
| Sound power level, outdoor | dB(A) | 64 |
| Sound power level, indoor | dB(A) | 64 |
| Annual energy consumption under colder climate conditions for medium-temperature applications (QHE) | kWh/a | 21670 |
| Annual energy consumption under average climate conditions for medium-temperature applications (QHE) | kWh/a | 14872 |
| Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE) | kWh/a | 9675 |
| Flow rate on heat source side | m³/h | 675 |