



ENERGY

tecalor

TTF 15.6 cool



55 °C

35 °C



39 dB



■ 14

■ 14

■ 14

kW

■ 15

■ 15

■ 15

kW



2019

811/2013



| | | TTF 15.6 cool |
|--|-------|---------------|
| | | 190610 |
| Manufacturer | | tecalor |
| Space heating energy efficiency class under average climate conditions, medium-temperature applications | | A+++ |
| Energy efficiency class, space heating under average climate conditions, low-temperature applications | | A+++ |
| Rated heating output under average climate conditions for medium-temperature applications (P rated) | kW | 14 |
| Rated heating output under average climate conditions for low-temperature applications (P rated) | kW | 15 |
| Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s) | % | 168 |
| Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s) | % | 210 |
| Annual energy consumption under average climate conditions for medium-temperature applications (QHE) | kWh/a | 6476 |
| Annual energy consumption under average climate conditions for low-temperature applications (QHE) | kWh/a | 5489 |
| Sound power level, indoor | dB(A) | 39 |
| Option for operation only at off-peak times | | - |
| Rated heating output under colder climate conditions for medium-temperature applications (P rated) | kW | 14 |
| Rated heating output under colder climate conditions for low-temperature applications (P rated) | kW | 15 |
| Rated heating output under warmer climate conditions for medium-temperature applications (P rated) | kW | 14 |
| Rated heating output under warmer climate conditions for low-temperature applications (P rated) | kW | 15 |
| Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s) | % | 174 |
| Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s) | % | 218 |
| Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s) | % | 167 |
| Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s) | % | 208 |
| Annual energy consumption under colder climate conditions for medium-temperature applications (QHE) | kWh/a | 7451 |
| Annual energy consumption under colder climate conditions for low-temperature applications (QHE) | kWh/a | 6298 |
| Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE) | kWh/a | 4211 |
| Annual energy consumption under warmer climate conditions for low-temperature applications (QHE) | kWh/a | 3573 |



ENERGY

tecalor

TTF 15.6 cool

| | | |
|---|--|-------------------------------------|
| + | | <input type="checkbox"/> |
| + | | <input type="checkbox"/> |
| + | | <input checked="" type="checkbox"/> |
| + | | <input type="checkbox"/> |




Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

| | | TTF 15.6 cool |
|---|---|----------------------|
| | | 190610 |
| Manufacturer | | tecalor |
| Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s) | % | 210 |
| Temperature control class | | VII |
| Contribution of temperature control to space heating energy efficiency | % | 4 |
| Space heating energy efficiency of package under average climate conditions | % | 171 |
| Space heating energy efficiency of package under colder climate conditions | % | 178 |
| Space heating energy efficiency of package under warmer climate conditions | % | 170 |
| Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions | % | 7 |
| Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions | % | 1 |
| Energy efficiency class, space heating under average climate conditions, low-temperature applications | | A+++ |
| Space heating energy efficiency class of package under average climate conditions | | A+++ |

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

| | | TTF 15.6 cool |
|--|----|----------------------|
| | | 190610 |
| Manufacturer | | tecalor |
| Heat source | | Sole |
| Low temperature heat pump | | - |
| With auxiliary heater | | x |
| Combination heater with heat pump | | - |
| Rated heating output under colder climate conditions for medium-temperature applications (P rated) | kW | 14 |
| Rated heating output under average climate conditions for medium-temperature applications (P rated) | kW | 14 |
| Rated heating output under warmer climate conditions for medium-temperature applications (P rated) | kW | 14 |
| Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 8,3 |
| Tj = -7 °C heating output, partial load range under average climate conditions (Pdh) | kW | 12,2 |
| Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 5,1 |
| Tj = 2 °C heating output, partial load range under average climate conditions (Pdh) | kW | 7,4 |
| Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh) | kW | 13,8 |
| Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 3,2 |
| Tj = 7 °C heating output, partial load range under average climate conditions (Pdh) | kW | 4,8 |
| Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh) | kW | 8,8 |
| Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh) | kW | 2,2 |
| Tj = 12 °C heating output, partial load range under average climate conditions (Pdh) | kW | 2,2 |
| Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh) | kW | 3,9 |
| Tj = dual mode temperature under colder climate conditions (Pdh) | kW | 13,8 |
| Tj = dual mode temperature under average climate conditions (Pdh) | kW | 13,8 |
| Tj = dual mode temperature under warmer climate conditions (Pdh) | kW | 13,8 |
| Tj = operating temperature limit under colder climate conditions (Pdh) | kW | 13,8 |
| Tj = operating temperature limit under average climate conditions (Pdh) | kW | 13,8 |
| Tj = operating temperature limit under warmer climate conditions (Pdh) | kW | 13,8 |
| Dual mode temperature under colder climate conditions (Tbiv) | °C | -22 |
| Dual mode temperature under average climate conditions (Tbiv) | °C | -10 |
| Dual mode temperature under warmer climate conditions (Tbiv) | °C | 2 |
| Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs) | % | 174 |
| Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs) | % | 168 |
| Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs) | % | 167 |
| Tj = -7 °C COP, partial load range under colder climate conditions (COPd) | | 4,24 |
| Tj = -7 °C COP, partial load range under average climate conditions (COPd) | | 3,40 |
| Tj = 2 °C COP, partial load range under colder climate conditions (COPd) | | 4,94 |
| Tj = 2 °C COP, partial load range under average climate conditions (COPd) | | 4,44 |
| Tj = 2 °C COP, partial load range under warmer climate conditions (COPd) | | 3,26 |
| Tj = 7 °C COP, partial load range under colder climate conditions (COPd) | | 5,24 |
| Tj = 7 °C COP, partial load range under average climate conditions (COPd) | | 5,03 |
| Tj = 7 °C COP, partial load range under warmer climate conditions (COPd) | | 3,99 |

| | | |
|--|-------------------|--------------|
| Tj = 12 °C COP, partial load range under colder climate conditions (COPd) | | 5,44 |
| Tj = 12 °C COP, partial load range under average climate conditions (COPd) | | 5,31 |
| Tj = 12 °C COP, partial load range under warmer climate conditions (COPd) | | 5,16 |
| Tj = dual mode temperature under colder climate conditions (COPd) | | 3,26 |
| Tj = dual mode temperature under average climate conditions (COPd) | | 3,26 |
| Tj = dual mode temperature under warmer climate conditions (COPd) | | 3,26 |
| Tj = operating temperature limit under colder climate conditions (COPd) | | 3,26 |
| Tj = operating temperature limit under average climate conditions (COPd) | | 3,26 |
| Tj = operating temperature limit under warmer climate conditions (COPd) | | 3,26 |
| Operating temperature limit under colder climate conditions (TOL) | °C | -22 |
| Operating temperature limit under average climate conditions (TOL) | °C | -10 |
| Operating temperature limit under warmer climate conditions (TOL) | °C | 2 |
| Operating temperature limit of heating water under colder climate conditions (WTOL) | °C | 75 |
| Operating temperature limit of heating water under average climate conditions (WTOL) | °C | 75 |
| Operating temperature limit of heating water under warmer climate conditions (WTOL) | °C | 75 |
| Power consumption, off-mode (Poff) | W | 19 |
| Power consumption, thermostat off-mode (PTO) | W | 19 |
| Power consumption, standby state (PSB) | W | 19 |
| Power consumption, operating state, with crankcase heating (PCK) | W | 0 |
| Rated heating output of auxiliary heater under colder climate conditions (PSUP) | kW | 0,0 |
| Rated heating output of auxiliary heater under average climate conditions (PSUP) | kW | 0,0 |
| Rated heating output of auxiliary heater under warmer climate conditions (PSUP) | kW | 0,0 |
| Type of energy supply, auxiliary heater | | elektrisch |
| Output control | | veränderlich |
| Sound power level, indoor | dB(A) | 39 |
| Annual energy consumption under colder climate conditions for medium-temperature applications (QHE) | kWh/a | 7451 |
| Annual energy consumption under average climate conditions for medium-temperature applications (QHE) | kWh/a | 6476 |
| Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE) | kWh/a | 4211 |
| Flow rate on heat source side | m ³ /h | 131 |