




# ENERGY

## tecalor

TTF 44.5



55 °C

35 °C



**50** dB



■ 36

■ 36

■ 36

kW

■ 38

■ 38

■ 38

kW



2019

811/2013



		<b>TTF 44.5</b>
		190779
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A+++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	36
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	38
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications ( $\eta_s$ )	%	168
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )	%	218
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	16768
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	13917
Sound power level, indoor	dB(A)	50
Option for operation only at off-peak times		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	36
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	38
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	36
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	38
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications ( $\eta_s$ )	%	174
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications ( $\eta_s$ )	%	226
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications ( $\eta_s$ )	%	167
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications ( $\eta_s$ )	%	220
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	19290
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	16014
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	10862
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	8920







# ENERGY

tecalor

TTF 44.5


+		<input type="checkbox"/>
+		<input type="checkbox"/>
+		<input checked="" type="checkbox"/>
+		<input type="checkbox"/>










**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

		<b>TTF 44.5</b>
		190779
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )	%	218
Temperature control class		II
Contribution of temperature control to space heating energy efficiency	%	2
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	6
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	1
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A+++

**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

		<b>TTF 44.5</b>
		190779
Manufacturer		tecalor
Heat source		Sole
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	36
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	36
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	36
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	21,6
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	31,5
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	13,1
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	19,2
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	35,6
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	12,6
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	12,3
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	22,9
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	12,6
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	12,6
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	12,5
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	35,6
Tj = dual mode temperature under average climate conditions (Pdh)	kW	12,4
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	35,6
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	35,6
Tj = operating temperature limit under average climate conditions (Pdh)	kW	35,6
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	35,6
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	35,6
Dual mode temperature under colder climate conditions (Tbiv)	°C	-22
Dual mode temperature under average climate conditions (Tbiv)	°C	-10
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	174
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	168
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	167
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		4,12
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		3,21
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		5,02
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		4,39
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,95
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		5,32
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		5,16
Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,89

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		5,49
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		534,00
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		5,17
Tj = dual mode temperature under colder climate conditions (COPd)		2,95
Tj = dual mode temperature under average climate conditions (COPd)		2,95
Tj = dual mode temperature under warmer climate conditions (COPd)		2,95
Tj = operating temperature limit under colder climate conditions (COPd)		2,95
Tj = operating temperature limit under average climate conditions (COPd)		2,95
Tj = operating temperature limit under warmer climate conditions (COPd)		2,95
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		2,21
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	65
Power consumption, off-mode (Poff)	W	7
Power consumption, thermostat off-mode (PTO)	W	7
Power consumption, standby state (PSB)	W	7
Power consumption, operating state, with crankcase heating (PCK)	W	0
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	0,0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, indoor	dB(A)	50
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	19290
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	16768
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	10862
Flow rate on heat source side	m³/h	975