



ENERGY

tecalor

TTF 12.5



55 °C

35 °C



A⁺⁺

A⁺⁺⁺



46 dB



0 dB

■ 14

■ 15

■ 14

kW

■ 15

■ 14

■ 15

kW



2019

811/2013

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTF 12.5
		190934
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	15
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	14
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	142
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	143
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	8167
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	5650
Sound power level, indoor	dB(A)	46
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	14
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	15
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	14
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	15
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	145
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)	%	147
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	143
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	144
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	9120
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	7049
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	4932
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	3922
Sound power level, outdoor	dB(A)	0






ENERGY


tecalor


TTF 12.5




+ 

+ 

+ 

+ 













Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTF 12.5
		190934
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	143
Temperature control class		III
Contribution of temperature control to space heating energy efficiency	%	2
Space heating energy efficiency of package under average climate conditions	%	143
Space heating energy efficiency of package under colder climate conditions	%	147
Space heating energy efficiency of package under warmer climate conditions	%	144
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	4
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	1
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A++

Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)

		TTF 12.5
		190934
Manufacturer		tecalor
Heat source		Sole
Low temperature heat pump		-
With auxiliary heater		x
Combination heater with heat pump		x
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	14
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	15
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	14
T _j = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	12,0
T _j = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	11,4
T _j = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	12,1
T _j = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	12,1
T _j = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	11,8
T _j = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	9,8
T _j = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	12,2
T _j = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	9,5
T _j = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	12,4
T _j = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	12,4
T _j = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	12,5
T _j = dual mode temperature under colder climate conditions (Pdh)	kW	11,9
T _j = dual mode temperature under average climate conditions (Pdh)	kW	11,9
T _j = dual mode temperature under warmer climate conditions (Pdh)	kW	11,9
T _j = operating temperature limit under colder climate conditions (Pdh)	kW	11,8
T _j = operating temperature limit under average climate conditions (Pdh)	kW	11,8
T _j = operating temperature limit under warmer climate conditions (Pdh)	kW	11,8
Dual mode temperature under colder climate conditions (T _{biv})	°C	-16
Dual mode temperature under average climate conditions (T _{biv})	°C	-5
Dual mode temperature under warmer climate conditions (T _{biv})	°C	4
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η _s)	%	145
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η _s)	%	142
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η _s)	%	143
T _j = -7 °C COP, partial load range under colder climate conditions (COPd)		3,63
T _j = -7 °C COP, partial load range under average climate conditions (COPd)		3,22
T _j = 2 °C COP, partial load range under colder climate conditions (COPd)		4,02
T _j = 2 °C COP, partial load range under average climate conditions (COPd)		3,76
T _j = 2 °C COP, partial load range under warmer climate conditions (COPd)		3,03
T _j = 7 °C COP, partial load range under colder climate conditions (COPd)		4,39
T _j = 7 °C COP, partial load range under average climate conditions (COPd)		4,10
T _j = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,50

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		4,70
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		4,53
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		4,22
Tj = dual mode temperature under colder climate conditions (COPd)		3,37
Tj = dual mode temperature under average climate conditions (COPd)		3,38
Tj = dual mode temperature under warmer climate conditions (COPd)		3,26
Tj = operating temperature limit under colder climate conditions (COPd)		3,03
Tj = operating temperature limit under average climate conditions (COPd)		3,03
Tj = operating temperature limit under warmer climate conditions (COPd)		3,03
Operating temperature limit of heating water under colder climate conditions (WTOL)	°C	65
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	65
Operating temperature limit of heating water under warmer climate conditions (WTOL)	°C	65
Power consumption, off-mode (Poff)	W	6
Power consumption, thermostat off-mode (PTO)	W	10
Power consumption, standby state (PSB)	W	10
Power consumption, operating state, with crankcase heating (PCK)	W	0
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	kW	2,3
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	2,9
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	kW	2,0
Type of energy supply, auxiliary heater		elektrisch
Sound power level, outdoor	dB(A)	0
Sound power level, indoor	dB(A)	46
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	9120
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	8167
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	4932
Flow rate on heat source side	m³/h	216