



ENERGY

tecalor

TTF 31.6 l topline



55 °C


35 °C



47 dB



0 dB



2019

811/2013

Product datasheet: Required details about space heater with heat pump to Regulation (EU) No 813/2013 & 811/2013 / (S.I. 2019 No. 539 / Programme 2)



		TTF 31.6 I topline
		191012
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A+++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	33
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	158
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	208
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	15756
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	12666
Sound power level, indoor	dB(A)	47
Option for operation only at off-peak times		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	33
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	33
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	165
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)	%	216
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	158
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	210
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	18097
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	14576
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	10211
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	8106
Sound power level, outdoor	dB(A)	0



ENERGY

TTF 31.6 l topline

tecalor

+		<input type="checkbox"/>
+		<input type="checkbox"/>
+		<input checked="" type="checkbox"/>
+		<input type="checkbox"/>



The diagram shows a vertical energy scale with seven levels, each represented by a colored arrow pointing to the right. From top to bottom, the levels are: A+++ (green), A++ (light green), A+ (yellow-green), A (yellow), B (orange), C (dark orange), D (red), E (dark red), F (red), and G (dark red). To the right of this scale is a black arrow pointing to the left, containing the text 'A+++', indicating the selected energy class.

Product datasheet: Required details about space heater with heat pump to Regulation (EU) No 813/2013 & 811/2013 / (S.I. 2019 No. 539 / Programme 2)

		TTF 31.6 I topline
		191012
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	208
Temperature control class		II
Contribution of temperature control to space heating energy efficiency	%	2
Space heating energy efficiency of package under average climate conditions	%	158
Space heating energy efficiency of package under colder climate conditions	%	165
Space heating energy efficiency of package under warmer climate conditions	%	158
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	7
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	0
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A+++

Product datasheet: Required details about space heater with heat pump to Regulation (EU) No 813/2013 & 811/2013 / (S.I. 2019 No. 539 / Programme 2)

		TTF 31.6 I topline
		191012
Manufacturer		tecalor
Heat source		Sole
Low temperature heat pump		-
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	32
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	19,2
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	28,0
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	11,7
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	17,1
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	31,7
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	11,7
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	11,0
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	20,4
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	11,7
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	11,7
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	11,6
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	31,7
Tj = dual mode temperature under average climate conditions (Pdh)	kW	31,7
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	31,7
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	31,7
Tj = operating temperature limit under average climate conditions (Pdh)	kW	31,7
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	31,7
Dual mode temperature under colder climate conditions (Tbiv)	°C	-22
Dual mode temperature under average climate conditions (Tbiv)	°C	-10
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	165
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	158
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	158
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		3,94
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		3,07
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		4,73
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		4,18
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,86
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		4,98
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		4,82

Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,73
Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		5,16
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		5,01
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		4,84
Tj = dual mode temperature under colder climate conditions (COPd)		2,86
Tj = dual mode temperature under average climate conditions (COPd)		2,86
Tj = dual mode temperature under warmer climate conditions (COPd)		2,86
Tj = operating temperature limit under colder climate conditions (COPd)		2,86
Tj = operating temperature limit under average climate conditions (COPd)		2,86
Tj = operating temperature limit under warmer climate conditions (COPd)		2,86
Operating temperature limit of heating water under colder climate conditions (WTOL)	°C	65
Operating temperature limit of heating water under average climate conditions (WTOL)	°C	65
Operating temperature limit of heating water under warmer climate conditions (WTOL)	°C	65
Power consumption, off-mode (Poff)	W	0
Power consumption, thermostat off-mode (PTO)	W	0
Power consumption, standby state (PSB)	W	0
Power consumption, operating state, with crankcase heating (PCK)	W	0
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	kW	0,0
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	0,0
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	kW	0,0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, outdoor	dB(A)	0
Sound power level, indoor	dB(A)	47
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	18097
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	15756
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	10211