



# ENERGY

## tecalor

TTF 42.6 l topline



55 °C

35 °C



**47** dB



■ 32

■ 32

■ 32

kW

■ 33

■ 33

■ 33

kW



2019

811/2013



		TTF 42.6 I topline
		191013
Manufacturer		tecalor
Space heating energy efficiency class under average climate conditions, medium-temperature applications		A+++
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	33
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications ( $\eta_s$ )	%	158
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )	%	208
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	15756
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	12666
Sound power level, indoor	dB(A)	47
Option for operation only at off-peak times		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	33
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	33
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications ( $\eta_s$ )	%	165
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications ( $\eta_s$ )	%	216
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications ( $\eta_s$ )	%	158
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications ( $\eta_s$ )	%	210
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	18097
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	14576
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	10211
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	8106



# ENERGY

*tecalor*

TTF 42.6 l topline


A+++

A++

A+

A

B

C

D

E

F

G



+ 

+ 

+ 

+ 

**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

		<b>TTF 42.6 I topline</b>
		191013
Manufacturer		tecalor
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications ( $\eta_s$ )	%	208
Temperature control class		II
Contribution of temperature control to space heating energy efficiency	%	2
Space heating energy efficiency of package under average climate conditions	%	160
Space heating energy efficiency of package under colder climate conditions	%	167
Space heating energy efficiency of package under warmer climate conditions	%	160
Energy efficiency class, space heating under average climate conditions, low-temperature applications		A+++
Space heating energy efficiency class of package under average climate conditions		A+++

**Product datasheet: Space heater to Regulation (EU) No 811/2013 (S.I. 2019 No. 539 / Programme 2)**

		<b>TTF 42.6 I topline</b>
		191013
Manufacturer		tecalor
Heat source		Sole
Low temperature heat pump		-
With auxiliary heater		-
Combination heater with heat pump		-
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	32
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	32
Tj = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	19,2
Tj = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	28,0
Tj = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	11,7
Tj = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	17,1
Tj = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	31,7
Tj = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	11,7
Tj = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	11,0
Tj = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	20,4
Tj = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	11,7
Tj = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	11,7
Tj = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	11,6
Tj = dual mode temperature under colder climate conditions (Pdh)	kW	31,7
Tj = dual mode temperature under average climate conditions (Pdh)	kW	31,7
Tj = dual mode temperature under warmer climate conditions (Pdh)	kW	31,7
Tj = operating temperature limit under colder climate conditions (Pdh)	kW	31,7
Tj = operating temperature limit under average climate conditions (Pdh)	kW	31,7
Tj = operating temperature limit under warmer climate conditions (Pdh)	kW	31,7
Dual mode temperature under colder climate conditions (Tbiv)	°C	-10
Dual mode temperature under average climate conditions (Tbiv)	°C	-22
Dual mode temperature under warmer climate conditions (Tbiv)	°C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (ηs)	%	165
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (ηs)	%	158
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (ηs)	%	158
Tj = -7 °C COP, partial load range under colder climate conditions (COPd)		3,94
Tj = -7 °C COP, partial load range under average climate conditions (COPd)		3,07
Tj = 2 °C COP, partial load range under colder climate conditions (COPd)		4,73
Tj = 2 °C COP, partial load range under average climate conditions (COPd)		4,18
Tj = 2 °C COP, partial load range under warmer climate conditions (COPd)		2,86
Tj = 7 °C COP, partial load range under colder climate conditions (COPd)		4,98
Tj = 7 °C COP, partial load range under average climate conditions (COPd)		4,82
Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3,73

Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		5,16
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		5,01
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		4,84
Tj = dual mode temperature under colder climate conditions (COPd)		2,86
Tj = dual mode temperature under average climate conditions (COPd)		2,86
Tj = dual mode temperature under warmer climate conditions (COPd)		2,86
Tj = operating temperature limit under colder climate conditions (COPd)		2,86
Tj = operating temperature limit under average climate conditions (COPd)		2,86
Tj = operating temperature limit under warmer climate conditions (COPd)		2,86
Power consumption, off-mode (Poff)	W	0
Power consumption, thermostat off-mode (PTO)	W	0
Power consumption, standby state (PSB)	W	0
Power consumption, operating state, with crankcase heating (PCK)	W	0
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	kW	0,0
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	0,0
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	kW	0,0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, indoor	dB(A)	47
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	18097
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	15756
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	10211