



**ENERG** Y IJA  
 енергия · ενέργεια IE IA

**STIEBEL ELTRON** WPE-I 05 HW 400 Plus



**A++**



**A**

42 dB



- 6 kW
- 6 kW
- 7 kW

2019

811/2013

**Product datasheet: Combi heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

		<b>WPE-I 05 HW 400 Plus</b>
		205834
Manufacturer		STIEBEL ELTRON
Load profile		XL
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Rated heating output in moderate climates for average temperature applications (Prated)	kW	6
Rated heating output in moderate climates for low temperature applications (Prated)	kW	6
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	3672
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	2630
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	135
Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )	%	181
Energy efficiency for DHW heating ( $\eta_{wh}$ ) under moderate climatic conditions	%	122
Sound power level internal	dB(A)	42
Rated heating output in colder climates for average temperature applications (Prated)	kW	6
Rated heating output in colder climates for low temperature applications (Prated)	kW	6
Rated heating output in warmer climates for average temperature applications (Prated)	kW	6
Rated heating output in warmer climates for low temperature applications (Prated)	kW	7
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	4104
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	3170
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2237
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	1825
Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )	%	138
Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )	%	187
Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )	%	135
Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )	%	183



# ENERG

енергия · ενέργεια

Y

IJA

IE

IA

**STIEBEL ELTRON**

WPE-I 05 HW 400 Plus

Energy label for heating system components. It shows a boiler icon with an **A++** rating, a radiator icon with an **A++** rating, and a tap icon with an **A** rating.

Energy label for a radiator. It features a radiator icon and a scale from **A+++** to **G**. The **A+++** rating is highlighted, and a black arrow points to **A++**.

Energy label for optional features. It lists four features with their respective energy ratings: solar panels (+), hot water storage tank (+), touch control panel (+), and a boiler (+). The touch control panel feature is marked with an **X** in a box.

Energy label for a tap. It features a tap icon with **XL** and a scale from **A+++** to **G**. The **A** rating is highlighted, and a black arrow points to **A**.

**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

		<b>WPE-I 05 HW 400 Plus</b>
		205834
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	135
Temperature controller class		III
Contribution of temperature controller to room heating energy efficiency	%	1
Room heating energy efficiency of composite system under moderate climatic conditions	%	136
Room heating energy efficiency of composite system under colder climatic conditions	%	139
Room heating energy efficiency of composite system under warmer climatic conditions	%	137
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++
Energy efficiency category for DHW heating under moderate climatic conditions		A
Load profile		XL

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		<b>WPE-I 05 HW 400 Plus</b>
		205834
Manufacturer		STIEBEL ELTRON
Heat source		Brine
Low temperature heat pump		-
With booster heater		x
Combi boiler with heat pump		x
Rated heating output in colder climates for average temperature applications (Prated)	kW	6
Rated heating output in moderate climates for average temperature applications (Prated)	kW	6
Rated heating output in warmer climates for average temperature applications (Prated)	kW	6
Tj = -7 °C heating output, partial load range in colder climates (Pdh)	kW	5.2
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	5.1
Tj = 2 °C heating output, partial load range in colder climates (Pdh)	kW	5.3
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	5.2
Tj = 2 °C heating output, partial load range in warmer climates (Pdh)	kW	5.0
Tj = 7 °C heating output, partial load range in colder climates (Pdh)	kW	5.4
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	5.3
Tj = 7 °C heating output, partial load range in warmer climates (Pdh)	kW	5.2
Tj = 12 °C heating output, partial load range in colder climates (Pdh)	kW	5.4
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	5.4
Tj = 12 °C heating output, partial load range in warmer climates (Pdh)	kW	5.3
Tj = dual mode temperature in colder climates (Pdh)	kW	5.1
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	5.1
Tj = dual mode temperature in warmer climates (Pdh)	kW	5.1
Tj = operating temperature limit in colder climates (Pdh)	kW	5.0
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	5.0
Tj = operating temperature limit in warmer climates (Pdh)	kW	5.0
Dual mode temperature in colder climates (Tbiv)	°C	-16
Dual mode temperature in moderate climates (Tbiv)	°C	-5
Dual mode temperature in warmer climates (Tbiv)	°C	4
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	138
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	135
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	135
Tj = -7 °C COP, partial load range in colder climates (COPd)		3.47
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		3.07
Tj = 2 °C COP, partial load range in colder climates (COPd)		3.86
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3.60
Tj = 2 °C COP, partial load range in warmer climates (COPd)		2.77
Tj = 7 °C COP, partial load range in colder climates (COPd)		4.17
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		3.94
Tj = 7 °C COP, partial load range in warmer climates (COPd)		3.34
Tj = 12 °C COP, partial load range in colder climates (COPd)		4.40
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		4.27
Tj = 12 °C COP, partial load range in warmer climates (COPd)		4.04
Tj = dual mode temperature in colder climates (COPd)		3.21
Tj = dual mode temperature under moderate climatic conditions (COPd)		3.21
Tj = dual mode temperature in warmer climates (COPd)		3.11

Tj = operating temperature limit in colder climates (COPd)		2.77
Tj = operating temperature limit under moderate climatic conditions (COPd)		2.77
Tj = operating temperature limit in warmer climates (COPd)		2.77
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	4
Power consumption, thermostat OFF state (PTO)	W	7
Standby power consumption (PSB)	W	7
Power consumption, operating state, with crankcase heating (PCK)	W	0
Booster heater heating output in colder climates (Psup)	kW	1.1
Booster heater heating output in moderate climate (Psup)	kW	1.3
Booster heater heating output in warmer climates (Psup)	kW	1.0
Type of energy supply, booster heater		electric
Sound power level internal	dB(A)	42
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	4104
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	3672
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2237
Flow rate, heat source side	m <sup>3</sup> /h	0,9
Load profile		XL
Daily power consumption in colder climates (QELEC)	kWh	6.396
Daily power consumption (Qelec)	kWh	6.396
Daily power consumption in warmer climates (QELEC)	kWh	6.396
Energy efficiency for DHW heating ( $\Gamma_{wh}$ ) under moderate climatic conditions	%	122