



ENERG Y IJA
 енергия · ενέργεια IE IA

STIEBEL ELTRON WPF 10 MS



55 °C

35 °C



A+

A++

51 dB

■ 11	■ 12
■ 9	■ 10
■ 9	■ 10
kW	kW

2015

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		WPF 10 MS
		222552
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Energy efficiency class for central heating in moderate climates for low temperature applications		A++
Rated heating output in moderate climates for medium temperature applications	kW	9
Rated heating output in moderate climates for low temperature applications	kW	10
Energy efficiency for central heating in moderate climates for medium temperature applications	%	124
Energy efficiency for central heating in moderate climates for low temperature applications	%	194
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	5719
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	4054
Sound power level internal	dB(A)	51
Rated heating output in colder climates for medium temperature applications	kW	11
Rated heating output in colder climates for low temperature applications	kW	12
Rated heating output in warmer climates for medium temperature applications	kW	9
Rated heating output in warmer climates for low temperature applications	kW	10
Energy efficiency for central heating in colder climates for medium temperature applications	%	129
Energy efficiency for central heating in colder climates for low temperature applications	%	201
Energy efficiency for central heating in warmer climates for medium temperature applications	%	125
Energy efficiency for central heating in warmer climates for low temperature applications	%	197
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	8239
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	5784
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	3663
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	2576



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

WPF 10 MS



A⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

+		<input type="checkbox"/>
+		<input type="checkbox"/>
+		<input checked="" type="checkbox"/>
+		<input type="checkbox"/>

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		WPF 10 MS
		222552
Manufacturer		STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications	%	124
Temperature controller class		VII
Contribution of temperature controller to room heating energy efficiency	%	3,5
Room heating energy efficiency of composite system under moderate climatic conditions	%	128
Room heating energy efficiency of composite system under colder climatic conditions	%	133
Room heating energy efficiency of composite system under warmer climatic conditions	%	129
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	5
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	1
Energy efficiency class for central heating in moderate climates for medium temperature applications		A+
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Product datasheet: Temperature controller to regulation (EU) no. 811/2013

		WPF 10 MS
		222552
Manufacturer		STIEBEL ELTRON
Heat source		Brine
{Niedertemperatur-Wärmepumpe}		-
With booster heater		-
Combi boiler with heat pump		-
Rated heating output in moderate climates for medium temperature applications	kW	9
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9,9
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	10,0
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	10,1
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	10,2
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	9,9
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	9,9
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	9,9
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		4,56
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		4,94
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		5,33
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		5,78
Tj = dual mode temperature under moderate climatic conditions (COPd)		4,50
Tj = operating temperature limit under moderate climatic conditions (COPd)		4,50
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		4,50
Dual mode temperature (Tbiv)	°C	-10
Heating water operating temperature limit (WTOL)	°C	60
Power consumption, OFF state (Poff)	W	0
Power consumption, thermostat OFF state (PTO)	W	5
Standby power consumption (PSB)	W	5
Power consumption, operating state, with crankcase heating (PCK)	W	0
Booster heater heating output (PSUB)	kW	0,00
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level internal	dB(A)	51
Flow rate, heat source side	m ³ /h	2,2