

|  |                           | <b>LA 60 AB</b> |
|--|---------------------------|-----------------|
|  |                           | 232123          |
| Manufacturer   |                           | STIEBEL ELTRON  |
| Specific energy consumption in colder climates, control subject to on-site requirements  | kWh/(m <sup>2</sup> p.a.) | -47,982         |
| Specific energy consumption in average climates, control subject to on-site requirements | kWh/(m <sup>2</sup> p.a.) | -22,899         |
| Specific energy consumption in warmer climates, control subject to on-site requirements  | kWh/(m <sup>2</sup> p.a.) | -8,531          |
| Energy efficiency class in average climates, control subject to on-site requirements     |                           | D               |
| Ventilation unit type  |                           | One direction   |
| Drive type   |                           | Variable speed  |
| Heat recovery method   |                           | None            |
| Rate of temperature change for heat recovery   | %                         | 0               |
| Max. air flow rate   | m <sup>3</sup> /h         | 60              |
| Max. power consumption   | W                         | 12              |
| Sound power level L <sub>wa</sub>  | dB(A)                     | 34              |
| Reference air flow rate  | m <sup>3</sup> /h         | 42              |
| Reference pressure differential  | Pa                        | 0               |
| Specific input   | W/(m <sup>3</sup> /h)     | 0,26            |
| Control factor, control subject to on-site requirements                                  |                           | 0,65            |
| Internal air leakage quota   | %                         | 0               |
| External air leakage quota   | %                         | 0               |
| Mixing quota   | %                         | 0               |
| Filter change indicator  |                           | Fascia          |
| {Anweisungen zu regelbaren Außenluftgittern bei ELA}                                     |                           | -               |
| Sensitivity to pressure fluctuations   | %                         | 0               |
| Internal and external air tightness  | m <sup>3</sup> /h         | 0,1             |
| Annual heating savings in colder climates with control subject to on-site requirements   | kWh/a                     | -41,22          |
| Annual heating savings in average climates with control subject to on-site requirements  | kWh/a                     | -21,07          |
| Annual heating savings in warmer climates with control subject to on-site requirements   | kWh/a                     | -9,53           |