



# ENERGY

**STIEBEL ELTRON**

WPL 09 IKCS classic  
comfort set



55 °C

35 °C



45 dB

32 dB

■ 7	■ 7
■ 4	■ 5
■ 2	■ 3

kW                      kW

2019

811/2013

**Product datasheet: Room heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

		<b>WPL 09 IKCS classic comfort set</b>
		236734
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Rated heating output in moderate climates for average temperature applications (Prated)	kW	4
Rated heating output in moderate climates for low temperature applications (Prated)	kW	5
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	128
Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )	%	175
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	2837
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	2178
Sound power level internal	dB(A)	45
Sound power level external	dB(A)	32
Rated heating output in colder climates for average temperature applications (Prated)	kW	7
Rated heating output in colder climates for low temperature applications (Prated)	kW	7
Rated heating output in warmer climates for average temperature applications (Prated)	kW	2
Rated heating output in warmer climates for low temperature applications (Prated)	kW	3
Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )	%	116
Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )	%	150
Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )	%	136
Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )	%	198
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	5547
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	4382
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	923
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	698









# ENERGY


**STIEBEL ELTRON**









WPL 09 IKCS classic comfort set



+    
 +    
 +    
 + 



**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

		<b>WPL 09 IKCS classic comfort set</b>
		236734
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )	%	128
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	132
Room heating energy efficiency of composite system under colder climatic conditions	%	120
Room heating energy efficiency of composite system under warmer climatic conditions	%	140
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	12
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	8
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		WPL 09 IKCS classic comfort set	
		236734	
Manufacturer		STIEBEL ELTRON	
Heat source		Outside air	
Low temperature heat pump		-	
Combi boiler with heat pump		x	
Rated heating output in colder climates for average temperature applications (Prated)	kW	7	
Rated heating output in moderate climates for average temperature applications (Prated)	kW	4	
Rated heating output in warmer climates for average temperature applications (Prated)	kW	2	
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	3.9	
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	2.5	
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	2	
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	2	
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	3.9	
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	3.9	
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	0	
Dual mode temperature in moderate climates (Tbiv)	°C	-7	
Seasonal room heating efficiency in colder climates for average temperature applications (ηs)	%	116	
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	128	
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	136	
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2.22	
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3.1	
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4.53	
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		6,44	
Tj = dual mode temperature under moderate climatic conditions (COPd)		2.22	
Tj = operating temperature limit under moderate climatic conditions (COPd)		2.22	
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		0	
Operating temperature limit in moderate climates (TOL)	°C	-7	
Heating water operating temperature limit (WTOL)	°C	60	
Power consumption, OFF state (Poff)	W	21	
Power consumption, thermostat OFF state (PTO)	W	56	
Standby power consumption (PSB)	W	56	
Power consumption, operating state, with crankcase heating (PCK)	W	26	
Booster heater heating output in moderate climate (Psup)	kW	1.54	
Type of energy supply, booster heater		electric	
Power control		variable	
Sound power level external	dB(A)	32	
Sound power level internal	dB(A)	45	
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	5547	
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	2837	
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	923	
Flow rate, heat source side	m <sup>3</sup> /h	1240	