



# ENERGY

**STIEBEL ELTRON**

WPL 13 ACS classic flex Set




55 °C

35 °C



57 dB



2019

811/2013

**Product datasheet: Room heater to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|   |   | <b>WPL 13 ACS classic flex Set</b> |
|---|---|------------------------------------|
|   |   | 239048                             |
| Manufacturer  |   | STIEBEL ELTRON                     |
| Energy efficiency class for central heating in moderate climates for medium temperature applications    |   | A++                                |
| Energy efficiency class for central heating in moderate climates for low temperature applications       |   | A+++                               |
| Rated heating output in moderate climates for average temperature applications (Prated)                 | kW  | 8                                  |
| Rated heating output in moderate climates for low temperature applications (Prated)                     | kW  | 7                                  |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ ) | %   | 125                                |
| Seasonal room heating efficiency in moderate climates for low temperature applications ( $\eta_s$ )     | %   | 177                                |
| Annual energy consumption in moderate climates for average temperature applications (QHE)               | kWh/a   | 4865                               |
| Annual energy consumption in moderate climates for low temperature applications (QHE)                   | kWh/a   | 3120                               |
| Sound power level external  | dB(A)   | 57                                 |
| Special measures  | For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions |                                    |
| Rated heating output in colder climates for average temperature applications (Prated)                   | kW  | 11                                 |
| Rated heating output in colder climates for low temperature applications (Prated)                       | kW  | 6                                  |
| Rated heating output in warmer climates for average temperature applications (Prated)                   | kW  | 6                                  |
| Rated heating output in warmer climates for low temperature applications (Prated)                       | kW  | 6                                  |
| Seasonal room heating efficiency in colder climates for average temperature applications ( $\eta_s$ )   | %   | 103                                |
| Seasonal room heating efficiency in colder climates for low temperature applications ( $\eta_s$ )       | %   | 151                                |
| Seasonal room heating efficiency in warmer climates for average temperature applications ( $\eta_s$ )   | %   | 153                                |
| Seasonal room heating efficiency in warmer climates for low temperature applications ( $\eta_s$ )       | %   | 213                                |
| Annual energy consumption in colder climates for average temperature applications (QHE)                 | kWh/a   | 10193                              |
| Annual energy consumption in colder climates for low temperature applications (QHE)                     | kWh/a   | 3713                               |
| Annual energy consumption in warmer climates for average temperature applications (QHE)                 | kWh/a   | 2048                               |
| Annual energy consumption in warmer climates for low temperature applications (QHE)                     | kWh/a   | 1556                               |









# ENERGY


**STIEBEL ELTRON**












WPL 13 ACS classic flex Set



+    
 +    
 +    
 + 



**Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013 / (S.I. 2019 No. 539 / Schedule 2)**

|   |   | <b>WPL 13 ACS classic flex Set</b> |
|---|---|------------------------------------|
|   |   | 239048                             |
| Manufacturer  |   | STIEBEL ELTRON                     |
| Seasonal room heating efficiency in moderate climates for average temperature applications ( $\eta_s$ )                                   | % | 125                                |
| Temperature controller class  |   | VI                                 |
| Contribution of temperature controller to room heating energy efficiency  | % | 4                                  |
| Room heating energy efficiency of composite system under moderate climatic conditions   | % | 129                                |
| Room heating energy efficiency of composite system under colder climatic conditions   | % | 107                                |
| Room heating energy efficiency of composite system under warmer climatic conditions   | % | 156                                |
| Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions | % | 22                                 |
| Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions | % | 27                                 |
| Energy efficiency class for central heating in moderate climates for medium temperature applications                                      |   | A++                                |
| Room heating energy efficiency class of composite system under moderate climatic conditions   |   | A++                                |

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

|   |    | WPL 13 ACS classic flex Set |
|---|----|-----------------------------|
|   |    | 239048                      |
| Manufacturer  |    | STIEBEL ELTRON              |
| Heat source   |    | Outside air                 |
| Low temperature heat pump   |    | -                           |
| With booster heater   |    | x                           |
| Combi boiler with heat pump   |    | -                           |
| Rated heating output in colder climates for average temperature applications (Prated)           | kW | 11                          |
| Rated heating output in moderate climates for average temperature applications (Prated)         | kW | 8                           |
| Rated heating output in warmer climates for average temperature applications (Prated)           | kW | 6                           |
| Tj = -7 °C heating output, partial load range in colder climates (Pdh)                          | kW | 6.6                         |
| Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 5.1                         |
| Tj = 2 °C heating output, partial load range in colder climates (Pdh)                           | kW | 4.0                         |
| Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 4.1                         |
| Tj = 2 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 6.0                         |
| Tj = 7 °C heating output, partial load range in colder climates (Pdh)                           | kW | 2.7                         |
| Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)           | kW | 2.6                         |
| Tj = 7 °C heating output, partial load range in warmer climates (Pdh)                           | kW | 3.9                         |
| Tj = 12 °C heating output, partial load range in colder climates (Pdh)                          | kW | 3.4                         |
| Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)          | kW | 3.3                         |
| Tj = 12 °C heating output, partial load range in warmer climates (Pdh)                          | kW | 3.3                         |
| Tj = dual mode temperature in colder climates (Pdh)   | kW | 6.6                         |
| Tj = dual mode temperature under moderate climatic conditions (Pdh)                             | kW | 6.1                         |
| Tj = dual mode temperature in warmer climates (Pdh)   | kW | 6.0                         |
| Tj = operating temperature limit in colder climates (Pdh)                                       | kW | 1.8                         |
| Tj = operating temperature limit under moderate climatic conditions (Pdh)                       | kW | 5.1                         |
| Tj = operating temperature limit in warmer climates (Pdh)                                       | kW | 6.0                         |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)                                   | kW | 0.0                         |
| Dual mode temperature in colder climates (Tbiv)   | °C | -7                          |
| Dual mode temperature in moderate climates (Tbiv)   | °C | -5                          |
| Dual mode temperature in warmer climates (Tbiv)   | °C | 2                           |
| Seasonal room heating efficiency in colder climates for average temperature applications (ηs)   | %  | 103                         |
| Seasonal room heating efficiency in moderate climates for average temperature applications (ηs) | %  | 125                         |
| Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)   | %  | 153                         |
| Tj = -7 °C COP, partial load range in colder climates (COPd)                                    |    | 2.40                        |
| Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 2.00                        |
| Tj = 2 °C COP, partial load range in colder climates (COPd)                                     |    | 3.60                        |
| Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 3.30                        |
| Tj = 2 °C COP, partial load range in warmer climates (COPd)                                     |    | 2.20                        |
| Tj = 7 °C COP, partial load range in colder climates (COPd)                                     |    | 5.00                        |
| Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)                     |    | 4.60                        |
| Tj = 7 °C COP, partial load range in warmer climates (COPd)                                     |    | 3.20                        |
| Tj = 12 °C COP, partial load range in colder climates (COPd)                                    |    | 6.20                        |
| Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)                    |    | 6                           |
| Tj = 12 °C COP, partial load range in warmer climates (COPd)                                    |    | 5.70                        |
| Tj = dual mode temperature in colder climates (COPd)  |    | 2.40                        |
| Tj = dual mode temperature under moderate climatic conditions (COPd)                            |    | 2.30                        |

|   |                   |          |
|---|-------------------|----------|
| Tj = dual mode temperature in warmer climates (COPd)                                      |                   | 2.20     |
| Tj = operating temperature limit in colder climates (COPd)                                |                   | 1.40     |
| Tj = operating temperature limit under moderate climatic conditions (COPd)                |                   | 2.00     |
| Tj = operating temperature limit in warmer climates (COPd)                                |                   | 2.20     |
| For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)                            |                   | 0.00     |
| Operating temperature limit in colder climates (TOL)                                      | °C                | -15      |
| Operating temperature limit in moderate climates (TOL)                                    | °C                | -5       |
| Operating temperature limit in warmer climates (TOL)                                      | °C                | 2        |
| Heating water operating temperature limit in colder climates (WTOL)                       | °C                | 60       |
| Heating water operating temperature limit (WTOL)  | °C                | 60       |
| Heating water operating temperature limit in warmer climates (WTOL)                       | °C                | 60       |
| Power consumption, OFF state (Poff)   | W                 | 17       |
| Power consumption, thermostat OFF state (PTO)   | W                 | 30       |
| Standby power consumption (PSB)   | W                 | 17       |
| Power consumption, operating state, with crankcase heating (PCK)                          | W                 | 5        |
| Booster heater heating output in colder climates (Psup)                                   | kW                | 11.0     |
| Booster heater heating output in moderate climate (Psup)                                  | kW                | 8.0      |
| Booster heater heating output in warmer climates (Psup)                                   | kW                | 0.0      |
| Type of energy supply, booster heater   |                   | electric |
| Power control   |                   | variable |
| Sound power level external  | dB(A)             | 57       |
| Annual energy consumption in colder climates for average temperature applications (QHE)   | kWh/a             | 10193    |
| Annual energy consumption in moderate climates for average temperature applications (QHE) | kWh/a             | 4865     |
| Annual energy consumption in warmer climates for average temperature applications (QHE)   | kWh/a             | 2048     |
| Flow rate, heat source side   | m <sup>3</sup> /h | 2200     |

Special measures

For all special measures to be taken during assembly, installation or maintenance of the room heater, see the installation instructions